

*Schroff*

## EuropacPRO kit, flexible design, unshielded, for backplane mounting



- Aluminum construction
- Subrack with side panel type F ("flexible"), 19" bracket is depth-adjustable
- Rear horizontal rail for backplane mounting with insulation strip
- Internal and external dimensions in accordance with: IEC 60297-3-100, -101, - 102, -103, - 104, -105, IEEE 1101.1, IEEE 1101.10/11
- IP 20, in accordance with IEC 60529
- EMC of approximately 40 dB at 1 GHz, 30 dB at 2 GHz, assuming that the front is covered with shielded front panels. Testing in accordance with VG 95373 part 15 or IEC 61587-3
- Modifications such as cutouts, different finishes or dimensions available
- Supplied as space-saving flat-pack

## Description

### **Load:**

Up to 11 kg

### **Shock/vibration:**

Up to 2 g

### **Design:**

EuropacPRO, Flexible

### **EMC Shielding:**

Unshielded  
Retrofitable

### **Type:**

Subrack Kit



Delivery Comprises:

<b>Item</b>	<b>Quantity</b>	<b>Description</b>
1	2	19" support bracket for EMC sealing (stainless steel)
2	2	Side panel type F
3a	2	Front horizontal rail (L-KD)
3b	2	Rear horizontal rail (L-ST) for backplane mounting with insulation strip
4	4	Threaded inserts, front and rear (pre-fitted)
5	2	Insulation strip (pre-fitted)
6	1	Assembly kit
7	1	User manual