



Product Description:

Application	For Signal Distribution and Security Markets
Reference Standard	Customer's sample spec. and the general standard
Multi-construction	A+B


Cable Construction:

Conductor	A	B
		Bare Copper
Construction	0.71 ±0.015	0.2 ±0.005 × 16
Standard Dia. (mm)	0.71	0.92
Insulation Layer	Foam PE	PVC
Thickness (mm)	1.27	0.43
Insulation Dia. (mm)	3.25 ±0.1	1.8 ±0.1 × 2
Colour	Natural	Red, Black
Al-Pet-Al Shielded	≥115%	-
Filler	-	Chalk
Braiding	Aluminium Wire	-
Construction	Al0.12 ±0.008 × 16 × 3	-
Braid coverage(%)	48%	-
Jacket	PVC	
Thickness (mm)	0.8	0.7
Dia.(±0.15mm)	6	5
Outer Jacket Colour	Black	
Marking	According to customer	
Packaging	#PP000638 - 100m/Wooden Drum	#PP000639 - 200m/Wooden Drum

Electrical Characteristics:

Max. Conductor DC Resistance at 20°C (Ω/Km)	
A	<47
B	<37
Min. Insulation DC Resistance at 20°C(MΩ*M)	>500
Rated Temperature (°C)	80
Rated Voltage (V)	30
Capacitance (pF/m)	54 ±3
Velocity ratio (%)	83%
Impedance (Ω)	75 ±3
Attenuation at 20°C (-dB/100m) (+/-5%)	
10MHz	3
50MHz	5.6
100MHz	7.9
230MHz	12.3
300MHz	14.2
400MHz	16
860MHz	24.7
1,000MHz	26.1

Design:



Part Number Table

Description	Part Number
Multicore, 3 Core, 100m, 30V, Black	PP000638
Multicore, 3 Core, 200m, 30V, Black	PP000639

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.