

# HEAVY DUTY ANTI-STATIC SOLUTION

**Product Code: HAS**

## PRODUCT DESCRIPTION

**Heavy Duty Anti-static Solution** controls the attraction of dirt, dust and bacteria on porous, absorbent and non-porous surfaces.

## PRODUCT USE

For use on non-porous surfaces where longer-term protection is required or where there is a high contamination level such as conveyor belts.

Use on absorbent surfaces such as fabric, chairs, clothing and carpets etc.

## FEATURES

- Prevents static build up on carpets and fabrics. Protects personnel from static 'shocks'.
- Guards against damage and destruction caused by static discharge.
- Added protection from static build up, which can ignite combustible vapours, powders and dusts causing explosions and fires.
- Effective at humidity levels as low as 3%.
- Does not degrade under thermal cycling.

## TOXICITY AND MATERIAL SAFETY


In ready to use form, **HAS** is non-toxic by oral ingestion, inhalation or dermal application, and is not a primary skin or major eye irritant.

When properly applied, **HAS** complies with or exceeds all electrostatic decay criteria established for anti-static performance as set forth by NFPA and MIL B-81705, when tested in accordance with Federal Test Standard 101B, Method 4046.

TECHNICAL  
DATA  
SHEET



**Copyright  
Electrolube 2002**  
All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## HEAVY DUTY ANTI-STATIC SOLUTION – Page 2

### TYPICAL PROPERTIES

Classification:	Anti-static
Form:	Liquid
Colour:	Very slight amber/clear
Approx. cloud point:	-1°C
Approx. solidification point:	-7°C
Solubility in water:	Complete
Dilution compatibility:	Water, hard or soft
Coverage for 5L:	250-300m <sup>2</sup>
Specific gravity 25°C:	.98
pH:	7-8
Odour:	Slight floral
Surface tension-reducing power:	Superior
Flammability:	None
Thermal cycling:	No effect
Temperature stability:	withstands up to 30 mins @ 230°C

### PACKAGING

1 litre bulk  
5 litre bulk

### ORDER CODE

HAS01L  
HAS05L

### TECHNICAL DATA SHEET



**Copyright  
Electrolube 2002**  
All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

