



Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

### 1 Identification of substance:

· Product details:

· Trade name: Cramolin Vaseline

· Article number: 114

Application of the substance / the preparation:
 Highly Viscous Lubricant with Anti-Corrosion Properties.

· Manufacturer/Supplier:

ITW Chemische Produkte GmbH Mühlacker Str. 149

D-75417 Mühlacker Tel: +49 7041 96340 Fax: +49 7041 963429 E-Mail: info@cramolin.de Internet: www.cramolin.de

· Informing department: Product safety department

· Emergency information:

ITW Chemische Produkte GmbH

Tel: +49 7041 96340

## 2 Composition/Data on components:

- · Chemical characterization
- · Description: Mixture of the substances listed below with harmless additions.

· components:		
CAS: 107-83-5	Isohexan	25-<50%
EINECS: 203-523-4	Xn, N F, N R 11-38-51/53-65-67	
CAS: 106-97-8	butane, pure	25-<50%
EINECS: 203-448-7		
CAS: 74-98-6	propane liquefied	10-<25%
EINECS: 200-827-9	<b>▶</b> F+; R 12	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-<10%
EINECS: 265-199-0	Xn, N; R 10-37-51/53-65	

· Additional information For the wording of the listed risk phrases refer to section 16.

### 3 Hazards identification

· Hazard designation:







- Xi Irritant
- F+ Extremely flammable
- N Dangerous for the environment

#### · Information pertaining to particular dangers for man and environment

The marking is valid for all pressurized container up to 50ml carrying capacity.

The product has to be labelled due to the calculation procedure of the "General Classification"

guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 38 Irritating to skin.

(Contd. on page 2)



Page 2/7

# **EU Material Safety Data Sheet** According to 91/155 EEC& 93/112 EWG

Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

Trade name: Cramolin Vaseline

(Contd. of page 1)

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

Classification system

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

## 4 First aid measures

- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

· After swallowing

Do not induce vomiting; instantly call for medical help.

A person vomiting while lying on their back should be turned onto their side.

### 5 Fire fighting measures

- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents Water.
- · Special hazards caused by the material, its products of combustion or resulting gases:

Formation of toxic gases is possible during heating or in case of fire.

Store in a cool place. Heat will increase pressure and may lead to the container exploding.

· Protective equipment:

Wear self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

· Additional information Cool endangered containers with water spray jet.

#### 6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Avoid contact with the eyes and skin.

· Measures for environmental protection:

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

Measures for cleaning/collecting:

Ensure adequate ventilation.

(Contd. on page 3)



Page 3/7

# **EU Material Safety Data Sheet** According to 91/155 EEC& 93/112 EWG

Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

Trade name: Cramolin Vaseline

(Contd. of page 2)

Do not flush with water or aqueous cleansing agents

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Additional information: See Section 7 for information on safe handling

## 7 Handling and storage

- · Handling
- · Information for safe handling:

Store in cool, dry place in tightly closed containers.

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Open and handle container with care.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

Do not spray on flames or red-hot objects.

- Storage
- · Requirements to be met by storerooms and containers:

Store in cool location.

Store only in the original container.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the container exploding.

### 8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Components with limit values that require monitoring at the workplace:

#### 107-83-5 Isohexan

TLV (European Union) Long-term value: 700 mg/m<sup>3</sup>, 200 ppm

## 106-97-8 butane, pure

OES (Great Britain) Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm

### 74-98-6 propane liquefied

OES (Great Britain) Asphyxiant

- · Additional information: The lists that were valid during the compilation were used as basis.
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while working.

(Contd. on page 4)





Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

Trade name: Cramolin Vaseline

(Contd. of page 3)

- Breathing equipment: Use breathing protection in case of insufficient ventilation.
- · Protection of hands:

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Tightly sealed safety glasses.

9 Physical and chemical p	roperties:			
· General Information				
Form: Colour: Odour:	Aerosol White Solvent-like			
<ul> <li>Change in condition         Melting point/Melting range: Not determined         Boiling point/Boiling range: -44°C     </li> </ul>				
· Flash point:	-97°C			
· Ignition temperature:	180°C			
· Self-inflammability:	Product is not self igniting.			
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ steam mixtures is possible.			
· Critical values for explosion:				
Lower:	1.1 Vol % 9.5 Vol %			
Upper:				
· Vapour pressure at 20°C:	7.7 hPa			
· Density at 20°C	0.655 g/cm³			
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix			
· Solvent content: Organic solvents:	82.4 %			
· Solids content:	17.6 %			



Page 5/7

# **EU Material Safety Data Sheet** According to 91/155 EEC& 93/112 EWG

Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

Trade name: Cramolin Vaseline

(Contd. of page 4)

## 10 Stability and reactivity

- · Thermal decomposition/ Conditions to be avoided: Protect from heat and direct sunlight.
- · Dangerous reactions Danger of bursting
- · Dangerous products of decomposition:

No dangerous products of decomposition if used and stored according to specifications.

## 11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

#### 107-83-5 Isohexan

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>190 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Slight irritant effect possible.
- · Sensitisation: No sensitising effect known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

### 12 Ecological information:

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Toxic for aquatic organisms

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

### 13 Disposal considerations

- · Product:
- · Recommendation Disposal must be made according to official regulations.
- · European waste catalogue

16 05 04 gases in pressure containers (including halons) containing dangerous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

GB





Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

**Trade name: Cramolin Vaseline** 

(Contd. of page 5)

# 14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID-GGVS/E Class: 2 5F Gases.

Kemler Number: 23
UN-Number: 1950
Packaging group: Label 2.1

Designation of goods: 1950 AEROSOLS (BUTANE, PROPANE)

· Maritime transport IMDG:



IMDG Class: 2.1
UN Number: 1950
Label 2.1
Packaging group: EMS Number: F-D.S-I

• EMS Number: F-D,S-U
• Marine pollutant: No

· Correct technical name: AEROSOLS (BUTANE, PROPANE)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 2.1 · UN/ID Number: 1950 · Label 2.1 · Packaging group: -

· Correct technical name: AEROSOLS, flammable (BUTANE, PROPANE)

# 15 Regulatory information

### · Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Directives and the Ordinance on Hazardous Materials (GefStoffV).

· Code letter and hazard designation of product:







Xi Irritant

F+ Extremely flammable

N Dangerous for the environment

### · Risk phrases:

- 12 Extremely flammable.
- 38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 7)





Printing date 17.05.2005 V - 2 Reviewed on 17.05.2005

Trade name: Cramolin Vaseline

(Contd. of page 6)

67 Vapours may cause drowsiness and dizziness.

#### · Safety phrases:

- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe fumes/aerosol.
- 33 Take precautionary measures against static discharges.
- 37 Wear suitable gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.
- 60 This material and its container must be disposed of as hazardous waste.

### · Special designation of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

- · National regulations
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

### 16 Other information:

Information is based on our current knowledge but does not establish a promise of product characteristics and does not substantiate any contractual legal relationship. Drawing of back-up data file for:

MSDS - Service - Center gmbH. Materiel-Safety-Data-Sheet Alemannenstrasse 49 6830 Rankweil AUSTRIA

Tel.: +43-(0)5522-60067 Fax.: +43-(0)5522-41031 E-Mail: office@msds.at www.msds.at

## · Relevant R-phrases

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 37 Irritating to respiratory system.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.
- · Contact: ITW Chemische Produkte GmbH, D-75417 Mühlacker
- · \* Data compared to the previous version altered. .