# EAO – Your Expert Partner for **Human Machine Interfaces**

### 82-4151.2243 - Illuminated pushbutton 16 mm stainless-steel, maintain

## 82-4151.2243 - Illuminated pushbutton 16 mm stainless-steel, maintain



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### Mounting

Design flush Mounting cut-out Ø 16 mm

#### **Front**

Front shape round
Front ring shape flush
Front dimension Ø 18 mm

#### Other Attributes

Operating voltage 12 V AC/DC Weight 0.021 kg
Operation current 14 mA

#### Operating-/Indication part

Lens optics opaque
Lens material Stainless steel
Lens profile flat
Lens illumination illuminative
Lens colour Stainless steel

#### **IP-Rating**

Front protection IP 67

#### **Connection Method**

Terminal Solder 2.8 x 0.5 mm

#### **Actuator**

Switching action Maintained

#### **Switching element**

Switching current 5 A
Contact material Silver
Contacts 1 C

Switching system Snap-action switching element

Switching voltage 250 V AC

#### Illumination

Illumination Dot with yellow LED

#### **Function**


Illuminated pushbutton

e a o


# EAO – Your Expert Partner for **Human Machine Interfaces**

### 82-4151.2243 - Illuminated pushbutton 16 mm stainless-steel, maintain


#### **Dimensions**




#### **Mounting cut-outs**



#### Wiring diagram



#### **Component layout**



#### Legend

Switching action: C = Maintained Contacts: C = Changeover