

Transformer Toroidal



RoHS
Compliant



Specifications:

Input Voltage : 230V \pm 10% 50/60Hz.
 DC resistance : 38.1 Ω \pm 15% @ 20°C
 Magnetising current : 5mA approx.@ 230V 50Hz

Losses

Iron loss : 0.519 Watts approx.
 Copper loss : 5.92 Watts Approx.
 Efficiency : 89% typical
 Temperature rise : 38°C approx.
 Ambient rated : 40°C


Temperature Class

Winding wire : Class H (180°C)
 Insulation system : Class B (130°C)
 Leadout insulation : Class A (105°C)
 Overall : Class A (105°C)

Approx. Dimensions/weight (mounting excluded)

Diameter : 80mm* allow extra 5mm
 Height : 34mm* over leadout area
 Weight : 0.84kg

Schematic



Transformer Toroidal



Termination

All leads Tri-Rated UL1015 style cable rated 600v /105°C VW-1. Primary leads double insulated with PVC sleeving for a minimum of 20mm. Lead lengths \pm 5mm approx. All leads ends tinned to 6 mm.

Pri/Sec leads 0°

Part Number Table:

Description	On Load Sec V	Rated amps per Sec	Off load Sec V	Sec Flex Gauge	Sec Ohms @ 20°C.	Part Number
Transformer, 50VA, 2 × 9V	9	2.78	10.2	20AWG	0.24	MCFE050/09
Transformer, 50VA, 2 × 12V	12	2.08	13.4	22AWG	0.41	MCFE050/12
Transformer Encaps. 50VA 2 × 15v	15	1.67	16.8	22AWG	0.64	MCFE050/15
Transformer, 50VA, 2 × 18V	18	1.39	20.2	22AWG	0.97	MCFE050/18
Transformer, 50VA, 2 × 25V	25	1	27.8	22AWG	1.72	MCFE050/25

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com

