	1		2		3	4	5		
		4.22±0.25 2.00±0.20 ±0.20	50±0.20	$11.20^{+0.10}_{-10}$ 11.20 $^{+0.10}_{-10}_{-10}$ 11.20 $^{+0.10}_{-10}_$	4-ø0.92±0.08 ∮2.30±0.08 ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓	D±0.05 K K D±0.05 K K N K D±0.05 K K N K N K N K N K N K N K N K	TERISTICS IG: UL94-V0 COPPER ALLOY MPED IELECTIVE GOLD I PLATED MATING CYCLES ATURE: -40 °C UP TO +105 °C FREE AND ROHS 5 A MAX 30 VAC INCE: >1000 MΩ ANDING VOLTAGE: 750 VAC/MIN CE: 20 mΩ MAX 964		В
F	RoHS Compliant]		PROJECTION:	GENERAL TOLERANCE				
					$.X = ^{+}/_{-} 0.2$				
L	09-AVR-15	PCB THIKNESS	QP						
ĸ	27-OCT-14	REVIEW	QL		.XX = ⁺ /_ 0.15				
J	21-AUG-13	DIM UPDATE		APPROVAL: NPr	UNIT: MM	DESCRIPTION: USB 2.0 TYPE B VERTICAL	SIZ	ZE	1
	15-FEV-13	DESIGNATION	AR		SCALE:		012		D
Н	08-NOV-11	CURRENT RATING	GG		SHEET: 1/2	WERI PART NO: 614 004 133 21	\	\4	
1 0	DATE	FILE	BY		DRAW:		~		1

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	toHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE			1
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĪK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	ld
В]	SCALE:			٢
A	10-SEP-14	PDF	QL]	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			