# **Detailed Specifications & Technical Data**



ENGLISH MEASUREMENT VERSION

## 19511 Portable Cordage - UL/CSA Types: SJTOW, STOW, SV, SVT



For more Information please call

1-800-Belden1



### **General Description:**

SJTOW Belflex® matte black premium PVC, 300V, 105°C, paper tape separator, smooth jacket, UL/CSA listed, international color code: light blue, brown, green/yellow.

hysical Characteristics (Overall)	
Conductor	
AWG: # Conductors AWG Stranding Conductor Material	
3 14 41x30 BC - Bare Copper	
Total Number of Conductors:	3
Type of Cordage:	SJTOW
nsulation	
Insulation Material Wall Thickness (in.)	
PVC - Polyvinyl Chloride 0.033	
Duter Shield	
Outer Shield Material Outer Shield Material	
Unshielded	
Outer Jacket	
Outer Jacket Material:	
Outer Jacket Trade Name Outer Jacket Material Belflex® PVC Blend - Polyvinyl Chloride Blend	Nom. Wall Thickness (in.)
Overall Cable Overall Cabling Color Code Chart:	
Color	
Blue	
Brown	
Green/Yellow	
Green/Yellow Overall Cabling Separator Material:	Paper Tape
	Paper Tape 0.380 in.
Overall Cabling Separator Material:	
Overall Cabling Separator Material:	
Overall Cabling Separator Material: Overall Nominal Diameter: Iechanical Characteristics (Overall)	0.380 in.
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:	0.380 in. -40°C To +105°C 87 lbs/1000 ft.
Overall Cabling Separator Material: Overall Nominal Diameter: Iechanical Characteristics (Overall) Operating Temperature Range:	0.380 in. -40°C To +105°C 87 lbs/1000 ft.
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         Applicable Specifications and Agency Compliance (	0.380 in. -40°C To +105°C 87 lbs/1000 ft.
Overall Cabling Separator Material: Overall Nominal Diameter: Iechanical Characteristics (Overall) Operating Temperature Range: Bulk Cable Weight: Applicable Specifications and Agency Compliance ( Applicable Standards & Environmental Programs	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall)
Overall Cabling Separator Material:         Overall Nominal Diameter:         International Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         Spplicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs NEC/(UL) Specification:	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW
Overall Cabling Separator Material:         Overall Nominal Diameter:         Overall Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs NEC/(UL) Specification:         CSA Specification:	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         pplicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs         NEC/(UL) Specification:         CSA Specification:         EU Directive 2011/65/EU (ROHS II):	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW Yes
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         spplicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs NEC/(UL) Specification:         CSA Specification:         EU Directive 2011/65/EU (ROHS II):         EU CE Mark:	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW Yes Yes
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         opplicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs NEC/(UL) Specification:         CSA Specification:         EU Directive 2011/65/EU (ROHS II):         EU Directive 2000/53/EC (ELV):	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW Yes Yes Yes
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         Bulk Cable Weight:         Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs NEC/(UL) Specification:         CSA Specification:         EU Directive 2011/65/EU (ROHS II):         EU Directive 2000/53/EC (ELV):         EU Directive 2002/95/EC (RoHS):	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW Yes Yes Yes Yes
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs NEC/(UL) Specification:         CSA Specification:         EU Directive 2011/65/EU (ROHS II):         EU Directive 2000/53/EC (ELV):         EU Directive 2002/95/EC (ROHS):         EU ROHS Compliance Date (mm/dd/yyyy):	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW Yes Yes Yes Yes Yes Output
Overall Cabling Separator Material:         Overall Nominal Diameter:         Iechanical Characteristics (Overall)         Operating Temperature Range:         Bulk Cable Weight:         Applicable Specifications and Agency Compliance (Applicable Standards & Environmental Programs         NEC/(UL) Specification:         CSA Specification:         EU Directive 2011/65/EU (ROHS II):         EU Directive 2000/53/EC (ELV):         EU Directive 2000/53/EC (ROHS):         EU RoHS Compliance Date (mm/dd/yyyy):         EU Directive 2002/96/EC (WEEE):	0.380 in. -40°C To +105°C 87 lbs/1000 ft. (Overall) SJTOW SJTOW Yes Yes Yes Yes Yes Otherwise of the second se

## **Detailed Specifications & Technical Data**



#### ENGLISH MEASUREMENT VERSION

### 19511 Portable Cordage - UL/CSA Types: SJTOW, STOW, SV, SVT

Flame Test							
UL Flame Test:			VW-1	VW-1			
CSA Flame Test:			FT1	FT1			
Plenum/Non-Plenum							
Plenum (Y/N):			No	No			
Surface Printing (O	verall)						
Electrical Characte	ristics (Overa	all)					
Max. Operating Voltage	- UL:						
Voltage 300 V RMS							
Max. Recommended Cur	rent:						
Current							
18 Amps per conducto	r @ 25°C						
13 Amps per conducto	r @ 25°C over 50 f	it.					
Dielectric Withstand	d Voltage:		2000 V AC Applied for	1 Min.			
Notes (Overall)							
Notes: Approved as	water resistant, oil	I resistant and outdoor us	e.				
Put Ups and Colors	s:						
Item #	Putup	Ship Weight	Color	Notes	Item Desc		
19511 B59250	250 FT	23.750 LB	BLACK, MATTE	С	3#14 PVC PVC SJTOW-A 105		
Notes:		1		I			
C = CRATE REEL PUT-U	P.						

Revision Number: 2 Revision Date: 01-06-2014

© 2015 Belden, Inc All Rights Reserved.

All Rights Reserved. Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information and belief at the date of its publication. The information provided in this Product Disclosure, is correct to the best of Belden's any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden belcares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.