✓
✓
O Horizontal PDU with
□
□
□
□
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓
✓</













Telecom & Networking

Data centres & Server farms

Broadcast & A/V

Industrial

Enterprise level power distribution for data centres and more

Looking for highperformance power distribution for your heavily loaded systems?

The newly developed LMS Data 13A heavy-duty horizontal high-density PDU using the UK plug input connector which is ideal for many device requirements including server, network and other industrial-type equipment functions such as broadcast and HVAC applications.

Combining a fully certified UK plug input combined with a compatible heavy load power flex means you can be assured this LMS Data PDU can work without problems, 24/7.

Furthermore, incorporated onto the horizontal form-factor are industry standard IEC-13 sockets, ideal for data, telco and broadcast equipment with the added benefit of integral electrical surge protection.

Robust in design, with an integral neon illuminated rocker switch for assured functionality, the LMS Data PDU is designed to deliver maximum electrical power today and tomorrow.

specifications:

Horizontal, high-density Power Distribution Unit (PDU)

UK plug style plug power input

Compatible, heavy-load power cable

6x IEC-13 output power sockets

Robust, black aluminium design for industrial use

Neon on/off power switch for assured control

Maximum power rating - 4000W

2.0 metre (approx.) power cordage

Ideal for data, telecom, broadcast and HVAC applications



* Image for representation only Subject to change



Copyright 2015 LMS Data All trademarks acknowledged E&OE. Details subject to change