

MST hub - DisplayPort to 4x DisplayPort

StarTech ID: MSTDP124DP



This MST hub lets you connect four monitors to your DisplayPort™ (DP) 1.2 equipped Windows® laptop or desktop.

Increase productivity with multiple screens

The newest generations of computers are more portable than ever, which often means that you're left with fewer video outputs and smaller integrated screens. This MST hub solves both of these problems by letting you connect four additional displays to your computer, which makes multitasking much easier.

Connect to any display

With the MST hub, you can use DisplayPort video adapters and cable adapters that enable you to connect HDMI, VGA or DVI displays. This ensures your MST hub will be compatible with virtually any television, monitor or projector. This MST hub is VESA and DisplayPort certified to support DP 1.2 enabled systems, for seamless integration with your existing video equipment.

Configure your displays for any environment

Using the MST hub, you can extend your desktop onto additional monitors and stream independent content to each display giving you the freedom to multitask and increase your productivity. You can also mirror the same image onto multiple displays for remote viewing applications such as digital signage.

Enjoy amazing video quality, without draining system resources

MST technology uses your existing video card to minimize the use of system resources while delivering Ultra HD 4K resolutions. This unprecedented performance makes MST perfect for high-resolution applications such as graphic design, gaming and medical imaging.



Spec Sheet

Note: When using a DisplayPort 1.1 video card the MST hub will act as a splitter, automatically mirroring your video source across all displays. Resolution limitations apply.

The MSTDP124DP supports plug-and-play installation for a hassle-free setup, and is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Note: MST shares 10.2 Gbps across all attached displays. Higher resolutions can restrict the available bandwidth with the remaining ports, please see our guideline below for determining an ideal resolution for your setup. Certain graphics adapters have limited MST support and will only output to three displays in total. If more than three monitors are attached the fourth will be disabled.

Average resolution bandwidth allocation:

1920x1080 (High-definition 1080p) @60hz - 22%

1920x1200 @60hz - 30%

2560x1440 @60hz - 35%

2560x1600 @60hz - 38%

3840 x 2160 (Ultra HD 4K) @30hz - 38%

Note: Exceeding 100% will reduce functionality.

Examples of supported resolution configurations:

Screen 1	Screen 2	Screen 3	Screen 4	Total % of
Resolution	Resolution	Resolution	Resolution	Bandwidth
1920x1080	1920x1080	1920x1080	1920x1080	88%
@60hz (22%)	@60hz (22%)	@60hz (22%)	@60hz (22%)	
1920x1200	1920x1080	1920x1080	1920x1080	96%
@60hz (30%)	@60hz (22%)	@60hz (22%)	@60hz (22%)	
3840x2160 @30hz (38%)	1920x1080 @60hz (22%)	1920x1080 @60hz (22%)	off	82%
3840x2160 @30hz (38%)	1920x1200 @30hz (30%)	1920x1080 @60hz (22%)	off	98%

Examples of unsupported resolution configurations

Screen 1	Screen 2	Screen 3	Screen 4	Total % of
Resolution	Resolution	Resolution	Resolution	Bandwidth
2560x1600	2560x1600	1920x1200	1920x1200	136%
@60hz (38%)	@60hz (38%)	@60hz (30%)	@60hz (30%)	130 /0
3840x2160	2560x1600	1920x1200	1920x1200	136%
@30hz (38%)	@60hz (38%)	@60hz (30%)	@60hz (30%)	130 /0
3840x2160	2560x1600	2560x1440	1920x1200	141%
@30hz (38%)	@60hz (38%)	@60hz (35%)	@60hz (30%)	14170
3840x2160	3840x2160	3840x2160	off	114%
@30hz (38%)	@30hz (38%)	@30hz (38%)	UII	1 14 70





Applications

- Build a four display video wall to present entertainment to your patrons with an impressive display at a restaurant or shopping center
- Use one screen for reference data such as websites, while composing a report on another screen
- Dock your DP 1.2 device and add four high-resolution displays to your workstation
- Create a panoramic video wall for DisplayPort digital signage applications
- Edit images, video or audio clips across four additional displays in any orientation or resolution
- · Perfect for spanning a spreadsheet/worksheet across additional displays, to avoid side-scrolling

Features

- Maximize your productivity by connecting four independent displays to your computer using the MST Hub
- Connect to almost any television, monitor or projector with the support of low-cost adapters
- Increase external video performance with support for resolutions up to 4K
- VESA and DisplayPort certified
- Compatible with DP1.2 graphics cards such as AMD Eyefinity Technology & AMD Radeon
- Plug-and-play installation
- Newly engineered chipset for increased compatibility



Technical Specifications

Warranty 2 Years Audio Yes

Chipset ID STDP4320
Converter Type MST Hub
Output Signal DisplayPort

Ports 4

Maximum Digital Resolutions 3840 x 2160 @30hz

Supported Resolutions 1024x768

1280x720 (High-definition 720p) 1920x1080 (High-definition 1080p)

1920x1200 2560x1440 2560x1600

3840 x 2160 (Ultra HD 4K) @30hz

Wide Screen Supported Yes

Connector A 1 - DisplayPort (20 pin) Male Input
Connector B 4 - DisplayPort (20 pin) Female Output

Color Black Enclosure Type Plastic

Product Height 0.6 in [15 mm]
Product Length 4.1 in [105 mm]
Product Weight 4.5 oz [127 g]
Product Width 2.6 in [65 mm]

Center Tip Polarity Positive Input Current 0.5 A

Input Voltage 110 ~ 240 AC

Output Current 3A
Output Voltage 5 DC
Plug Type N

Power Source AC Adapter Included

Operating Temperature 0°C to 45°C (32°F to 113°F)
Storage Temperature -20°C to 70°C (-4°F to 158°F)

Shipping (Package) Weight 1.2 lb [0.5 kg]

Included in Package 1 - 4-Port Multi Monitor DisplayPort™ MST Hub



Hard-to-find made easy®

Spec Sheet

Included in Package

- 1 Universal power adapter (NA/EU/UK/AUS)
- Included in Package 1 Quick install guide

Certifications, Reports and Compatibility







