

www.tripplite.com



# Power It! 3-Outlet Power Strip, 6-ft. Cord

### MODEL NUMBER: TLM306NC





#### Description

Tripp Lite's Power It! TLM306NC power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment. Includes 3 NEMA 5-15R outlets, 6-foot AC power cord and keyhole mounting slots. Multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged metal case to stand up to the most demanding environments, illuminated power switch with transparent cover to prevent accidental shutoff and 15A integrated circuit breaker to prevent dangerous overloads.

INPUT/OUTPUT: Input: NEMA 5-15P/Output: 3 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: Corded power distribution strip

## Features

- Multi-outlet power strip offers reliable, convenient and cost-effective power distribution for appliances, power tools, lighting and other electrical equipment
- Includes 3 NEMA 5-15R outlets
- Illuminated on/off switch provides one-touch power control for connected equipment
- Transparent switch cover snaps tight to prevent accidental shutoff
- Convenient keyhole slots provide secure mounting options for a wide variety of surfaces and applications
- 15A power handling capacity with integrated circuit breaker
- 120V AC, 50/60Hz electrical compatibility
- 6-foot AC power cord
- · Rugged metal case provides extra safety and durability
- UL certification

# **Specifications**

### **Highlights**

- 3 outlets
- Illuminated on/off switch with cover
- 15-amp circuit breaker
- 6 ft. power cord
- Rugged metal case
- . Keyhole mounting slots

#### **Applications**

- Offers a reliable, convenient and cost-effective method of power distribution for appliances, power tools, lighting and other electrical equipment in home, office or worksite.
- Unfiltered electrical pass-through makes the power strip ideal for distributing alternate waveform UPS or generator power to connected equipment.

### **Package Includes**

- TLM306NC power strip
- Warranty information
- Instruction manual



OUTPUT         Frequency Compatibility         50 / 60 Hz           Output Receptacies         (3) 5-15R           Output (Waits)         1800           Circuit Breaker (amps)         15           Overlaad Protection         15A circuit breaker           Outlet Orientation         Single row of 3           20-Amp Rating         No           INPUT           Recommended Electrical Service           Input Connection Type         NEMA 5-15P           Input Cord Length (ft)         6           Input Cord Cauge Type         3T 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           User INTERFACE, ALERT'S & CONTEXT           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps tight to prevent accidental shutoff           PVYSICAL           Shipping Dimensions (ftwd / rm)         10 x 5 x 2 1           Shipping Weight (tbs.)         1.6           Shipping Weight (tb)         7           Lint Dimensions (ftwd / rm)         8.75 x 2 5 x 2           Unit Universion (ftwd / rm)         8.75 x 2 5 x 2           Unit Weight (kg)         6 <th></th> <th></th>			
Output Receptacles         (3) 5-15R           Output (Watts)         1800           Circuit Breaker (amps)         15           Overload Protection         15A circuit breaker           Outlet Orientation         Single row of 3           2x-Amp Rating         No           INPUT           Nominal Input Voltage(s) Supported         120V AC           Recommended Electrical Service         15A 120V           Input Cornection Type         NEMA 5-15P           Input Cord Length (ft.)         6           Input Cord Gauge Type         SJT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & CONTROLS           Switches         Illuminated orioff switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps tight to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (mvd / in.)         10 x 5 x 2 .1           Shipping Weight (bs.)         1.6           Shipping Weight (bs.)         2.5 4 x 14 x 5.3           Shipping Weight (kg)         7           Unit Dimensions (twd / in.)         8.75 x 2.5 x 2           Unit Unimposition (twd / in.)	ОИТРИТ		
Output (Watts)         1800           Circuit Breaker (amps)         15           Overload Protection         15A circuit breaker           Outlet Orientation         Single row of 3           20-Amp Rating         No           INPUT           Neminal Input Voltage(s) Supported           Recommended Electrical Service         15A 120V           Input Corn Length (ft)         6           Input Cord Length (ft)         6           Input Cord Length (m)         1.8           Input Cord Gauge Type         SUT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & Control           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps light to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (thw/d / in.)         10 x 5.x x 2.1           Shipping Weight (fks)         1.8           Shipping Weight (fks)         7           Unit Dimensions (thw/d / om)         25.4 x 14 x 5.3           Shipping Weight (kg)         7           Unit Ubingensions (thw/d / om)         22.2 x 6.4 x 5.1	Frequency Compatibility	50 / 60 Hz	
Circuit Breaker (amps)         15           Overload Protection         15A circuit breaker           Quited Orientation         Single row of 3           20-Amp Rating         No           INPUT           Nominal Input Voltage(s) Supported         120V AC           Recommended Electrical Service         15A 120V           Input Cornection Type         NEMA 5-15P           Input Cord Length (ft)         6           Input Cord Length (ft)         1.8           Input Cord Gauge Type         ST1 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & COVENTION           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps light to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (hwd / in.)         10 x 5. x 2.1           Shipping Dimensions (hwd / cm)         25.4 x 14 x 5.3           Shipping Weight (bs.)         1.6           Shipping Weight (kg)         7           Unit Dimensions (hwd / cm)         22 x 6 4 x 5.1           Unit Dimensions (hwd / cm)         22 x 6 4 x 5.1           Unit Usinghit	Output Receptacles	(3) 5-15R	
Overload Protection         15A circuit breaker           Outlet Orientation         Single row of 3           20-Amp Rating         No           INPUT           Nominal Input Voltage(s) Supported         120 V AC           Recommended Electrical Service         15A 120 V           Input Cornection Type         NEMA 5-15P           Input Cord Length (ft)         6           Input Cord Sauge Type         SJT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & CONTACT           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps tight to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (hwd / in.)         10 x 5 x 2.1           Shipping Weight (lbs.)         1.6           Shipping Weight (lbs.)         1.6           Shipping Weight (lbs.)         8.75 x 2.5 x 2           Unit Dimensions (hwd / in.)         8.75 x 2.5 x 2           Unit Universions (hwd / in.)         8.75 x 2.5 x 2           Unit Universions (hwd / in.)         8.75 x 2.5 x 2           Unit Universions (hwd / in.)         8.75 x 2.5 x 2	Output (Watts)	1800	
Outlet Orientation         Single row of 3           20-Amp Rating         No           INPUT           Nominal Input Voltage(s) Supported         120V AC           Recommended Electrical Service         15A 120V           Input Cornection Type         NEMA 6-15P           Input Cord Length (ft)         6           Input Cord Gauge Type         SJT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & CONTRACT           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps light to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (hwd / in.)         10 x 5.5 x 2.1           Shipping Weight (lbs.)         1.6           Shipping Weight (lbs.)         7           Unit Dimensions (hwd / cm)         25.4 x 14 x 5.3           Unit Dimensions (hwd / cm)         22.2 x 6.4 x 5.1           Unit Dimensions (hwd / cm)         22.2 x 6.4 x 5.1           Unit Dimensions (hwd / cm)         22.2 x 6.4 x 5.1           Unit Weight (lbs.)         6           Material of Construction         Metal case           Int	Circuit Breaker (amps)	15	
Amp Rating         No           INPUT           Nominal Input Voltage(s) Supported         120V AC           Recommended Electrical Service         15A 120V           Input Cornection Type         NEMA 5-15P           Input Cord Length (ft.)         6           Input Cord Length (m)         1.8           Input Cord Gauge Type         SUT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & CONTROLS           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps tight to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (ftwd / in.)         10 x 5.5 x 2.1           Shipping Dimensions (ftwd / in.)         1.6           Shipping Weight (bs.)         1.6           Shipping Weight (kg)         7           Unit Dimensions (ftwd / in.)         8.75 x 2.5 x 2           Unit Universions (ftwd / in.)         2.2 x 6.4 x 5.1           Unit Weight (kg.)         6           Material of Construction         Metal case           Interpreted Keyhole Mounting Tabs         Keyhole slots enable mounting to a variety of surfaces <td>Overload Protection</td> <td>15A circuit breaker</td>	Overload Protection	15A circuit breaker	
INPUT  Nominal Input Voltage(s) Supported   120V AC   Recommended Electrical Service   15A 120V   Input Connection Type   NEMA 5-15P   Input Cord Length (ft.)   6   Input Cord Gauge Type   SJT 14AWG   Input Cord Gauge Type   SJT 14AWG   Voltage Compatibility (VAC)   120   GFCI Plug   Yes    USER INTERFACE, ALERTS & CONTUS   Switches   Illuminated on/off switch controls power to all outlets   Locking Switch Cover   Transparent switch cover snaps light to prevent accidental shutoff    PHYSICAL  Shipping Dimensions (ftwd / cm)   10 x 5.5 x 2.1   Shipping Dimensions (ftwd / cm)   25 4 x 14 x 5.3   Shipping Weight (lbs.)   1.6   Shipping Weight (kg)   7   Unit Dimensions (ftwd / cm)   2.2 x 6.4 x 5.1   Unit Dimensions (ftwd / cm)   2.2 x 6.4 x 5.1   Unit Weight (kg)   1.4   Unit Weight (kg)   6   Material of Construction   Metal case   Integrated Keyhole Mounting Tabs   Keyhole slots enable mounting to a variety of surfaces	Outlet Orientation	Single row of 3	
Nominal Input Voltage(s) Supported         120V AC           Recommended Electrical Service         15A 120V           Input Connection Type         NEMA 5-15P           Input Cord Length (ft.)         6           Input Cord Length (m)         1.8           Input Cord Gauge Type         SJT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & CONTOLS           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps tight to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (hwd / in.)         10 x 5.5 x 2.1           Shipping Weight (lbs.)         1.6           Shipping Weight (kg.)         .7           Unit Dimensions (hwd / in.)         8.75 x 2.5 x 2           Unit Dimensions (hwd / cm)         2.2 x 6.4 x 5.1           Unit Weight (kg.)         1.4           Unit Weight (kg.)         6           Material of Construction         Metal case           Integrated Keyhole Mounting Tabs         Keyhole slots enable mounting to a variety of surfaces	20-Amp Rating	No	
Recommended Electrical Service         15A 120V           Input Connection Type         NEMA 5-15P           Input Cord Length (ft.)         6           Input Cord Length (m)         1.8           Input Cord Gauge Type         SJT 14AWG           Voltage Compatibility (VAC)         120           GFCI Plug         Yes           USER INTERFACE, ALERTS & CONTROLS           Switches         Illuminated on/off switch controls power to all outlets           Locking Switch Cover         Transparent switch cover snaps tight to prevent accidental shutoff           PHYSICAL           Shipping Dimensions (hwd / in.)         10 x 5.5 x 2.1           Shipping Weight (lbs.)         1.6           Shipping Weight (kbs.)         7           Unit Dimensions (hwd / in.)         8.75 x 2.5 x 2           Unit Dimensions (hwd / rom)         22.2 x 6.4 x 5.1           Unit Weight (kg)         .6           Material of Construction         Metal case           Integrated Keyhole Mounting Tabs         Keyhole slots enable mounting to a variety of surfaces	INPUT		
Input Connection Type Input Cord Length (ft.) Input Cord Length (m) Input Cord Gauge Type SJT 14AWG Voltage Compatibility (VAC) ICPUT VOLTAGE SST 14AWG Voltage Compatibility (VAC) ICPUT VOLTAGE VER INTERFACE, ALERTS & CONTOLS  Witches Illuminated on/off switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) Inspiring Dimensions (hwd / orn) Inspiring Weight (bs.) Inspiring Weight (kg) Institute Dimensions (hwd / orn) Instit	Nominal Input Voltage(s) Supported	120V AC	
Input Cord Length (fit.) 6 Input Cord Length (m) 1.8 Input Cord Gauge Type SJT 14AWG  Voltage Compatibility (VAC) 120  GFCI Plug Yes  USER INTERFACE, ALERTS & CONTOLS  Switches Illuminated on/off switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1 Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3 Shipping Weight (lbs.) 1.6 Shipping Weight (kg) .7 Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1 Unit Weight (kg) .6 Material of Construction Metal case Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Recommended Electrical Service	15A 120V	
Input Cord Length (m) Input Cord Gauge Type SJT 14AWG  Voltage Compatibility (VAC) 120  GFCI Plug Yes  WER INTERFACE, ALERTS & CONTROLS  Switches Illuminated on/off switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) 7  Unit Dimensions (hwd / in.) 8.75 x 2.5 x 2  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) 6  Material of Construction Metal case Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Input Connection Type	NEMA 5-15P	
Input Cord Gauge Type SJT 14AWG  Voltage Compatibility (VAC) 120  GFCI Plug Yes  VSER INTERFACE, ALERTS & CONTOLS  Switches Illuminated on/off switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Meterial of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Input Cord Length (ft.)	6	
Voltage Compatibility (VAC)  GFCI Plug  Yes  Vase  Vas	Input Cord Length (m)	1.8	
USER INTERFACE, ALERTS & CONTROLS  Switches Illuminated on/off switch controls power to all outlets  Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / in.) 8.75 x 2.5 x 2  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Input Cord Gauge Type	SJT 14AWG	
USER INTERFACE, ALERTS & CONTROLS  Switches Illuminated on/off switch controls power to all outlets Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / in.) 8.75 x 2.5 x 2  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Voltage Compatibility (VAC)	120	
Switches Illuminated on/off switch controls power to all outlets  Locking Switch Cover Transparent switch cover snaps tight to prevent accidental shutoff  PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	GFCI Plug	Yes	
PHYSICAL Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1 Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3 Shipping Weight (lbs.) 1.6 Shipping Weight (kg) 7 Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1 Unit Umensions (hwd / cm) 22.2 x 6.4 x 5.1 Unit Weight (lbs.) 1.4 Unit Weight (kg) 6 Material of Construction Metal case Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	USER INTERFACE, ALERTS & CONTROLS		
PHYSICAL  Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / in.) 8.75 x 2.5 x 2  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs	Switches	Illuminated on/off switch controls power to all outlets	
Shipping Dimensions (hwd / in.) 10 x 5.5 x 2.1  Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / in.) 8.75 x 2.5 x 2  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Locking Switch Cover	Transparent switch cover snaps tight to prevent accidental shutoff	
Shipping Dimensions (hwd / cm) 25.4 x 14 x 5.3  Shipping Weight (lbs.) 1.6  Shipping Weight (kg) .7  Unit Dimensions (hwd / in.) 8.75 x 2.5 x 2  Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	PHYSICAL		
Shipping Weight (lbs.)  Shipping Weight (kg)  .7  Unit Dimensions (hwd / in.)  8.75 x 2.5 x 2  Unit Dimensions (hwd / cm)  22.2 x 6.4 x 5.1  Unit Weight (lbs.)  1.4  Unit Weight (kg)  6  Material of Construction  Metal case  Integrated Keyhole Mounting Tabs  Keyhole slots enable mounting to a variety of surfaces	Shipping Dimensions (hwd / in.)	10 x 5.5 x 2.1	
Shipping Weight (kg)  Unit Dimensions (hwd / in.)  8.75 x 2.5 x 2  Unit Dimensions (hwd / cm)  22.2 x 6.4 x 5.1  Unit Weight (lbs.)  1.4  Unit Weight (kg)  6  Material of Construction  Metal case  Integrated Keyhole Mounting Tabs  Keyhole slots enable mounting to a variety of surfaces	Shipping Dimensions (hwd / cm)	25.4 x 14 x 5.3	
Unit Dimensions (hwd / in.)  8.75 x 2.5 x 2  Unit Dimensions (hwd / cm)  22.2 x 6.4 x 5.1  Unit Weight (lbs.)  1.4  Unit Weight (kg)  6  Material of Construction  Metal case  Integrated Keyhole Mounting Tabs  Keyhole slots enable mounting to a variety of surfaces	Shipping Weight (lbs.)	1.6	
Unit Dimensions (hwd / cm) 22.2 x 6.4 x 5.1  Unit Weight (lbs.) 1.4  Unit Weight (kg) .6  Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Shipping Weight (kg)	.7	
Unit Weight (lbs.)  1.4  Unit Weight (kg)  6  Material of Construction  Metal case  Integrated Keyhole Mounting Tabs  Keyhole slots enable mounting to a variety of surfaces	Unit Dimensions (hwd / in.)	8.75 x 2.5 x 2	
Unit Weight (kg)  6  Material of Construction  Metal case  Integrated Keyhole Mounting Tabs  Keyhole slots enable mounting to a variety of surfaces	Unit Dimensions (hwd / cm)	22.2 x 6.4 x 5.1	
Material of Construction Metal case  Integrated Keyhole Mounting Tabs Keyhole slots enable mounting to a variety of surfaces	Unit Weight (lbs.)	1.4	
Integrated Keyhole Mounting Tabs  Keyhole slots enable mounting to a variety of surfaces	Unit Weight (kg)	.6	
	Material of Construction	Metal case	
Receptacle Color Light Gray	Integrated Keyhole Mounting Tabs	Keyhole slots enable mounting to a variety of surfaces	
	Receptacle Color	Light Gray	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Color (AC Line Cord)	Light Gray	
Outlets Measurement (Center to Center)	40.49mm	
Keyhole Slot Mounting Measurement (Center to Center)	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm	
CERTIFICATIONS		
Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies