Flat Telephone Cable 24 AWG, 6 Stranded Conductors Multicomp







Description

Bare Copper Stranded, Polypropylene Insulated, Telephone Flat Cable. PVC Jacket

Specifications

Temperature & Voltage Rating : 60°C to 150V

Conductor Resistance : 93 Ohms / 1,000 Meters Max. at 20°C Insulation Resistance : $100M\Omega$ / 1,000 Meters Min. at 20°C


: 500V AC for One Min. Dielectric Strength

Insulation:

Conductor	Insulation		Colour Code		
AMG	Material	O.D.	1. White	2. Black	3. Red
24 (11 / 0.16)	PP	0.95 ± 0.05mm	4. Green	5. Yellow	6. Blue

Jacket:

Material	O.D.	Colour
PVC	2.4 × 7.0 ± 0.1mm	Silver Satin



Part Number Table

Description	Packaging	Part Number
Flat Telephone Cable, 24 AWG,	Shrink Wrapped Roll	SPC19814-RH
6 Stranded Conductors, 500ft	Spool	SPC19814-SL

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

