Power Cord



Specifications:

Insulation Material

Cable Length - Imperial : 6.6 Ft
Cable Length - Metric : 2m

Connector Type A : Mains Plug, UK
Connector Type B : Free Ends
Jacket Colour : Black
Cord Type : H05VV-F
Shielding Material : PVC
Insulation(Single or Double) : Single

Conductor Type : Annealed Soft Bare copper

: PVC

Number of Conductors : 3

Conductor Size : 0.75mm²


Conductor Construction : 24/0.2


Cord Jacket Diameter : 6.6 ±0.2

Voltage Rating : 250V


Current rating : 10A

Temperature Rating : 70°C










Dimensions : Millimetres

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



Power Cord





INDENT MARKING:

GFC-3R ▷ VDE ▷ KEMA-KEUR □ SEMKO ▷ DEMKO ▷ □ NEMKO ▷ □ FIMKO ▷ □ CEBEC618 ▷ □ ○ ○ □ ▷ + ∞ + ∞ + ∞ IEMMEQU NF-USE-1291-H05VV-F 3G 0.75mm²

Dimensions: Millimetres

Notes:

- 1. Cable: The cord shall comply with IEC60227
- 2. Plug: The Molded plug shall comply with BS1363A and Fuse shall comply with BS1362
- 3. The product shall be tested 100% for all safety electrical items

Part Number Table

Description	Part Number
Power Cord, UK Plug-Free End, 2m	GW-151629

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

