


Micro B Female to USB C Male Adapter USB 2.0



Electrical Character

Hi-POT : DC300V 10ms
 Insulation Resistance : 5MΩ Min.
 Contact Resistance : 2Ω Max.
 100% Open and Short Test



No.	Part Name	Description
1.	Connector 1	USB2.0 Micro B Type Female Pin G/F, Shell Plated Nickel
2.	Connector 2	USB3.1 C Type Male Pin G/F, Shell Plated Nickel
3.	PCB	USB C Male to Micro B/F PCBA
4.	Inner Mold	LD-PE
5.	Over Mold	PVC 70Pa Black

PIN ASSIGNMENT

SINGNAL	P1	COLOUR	Conn.2	SINGNAL
VBUS	A4,B4,A9,B9	RED	1	VBUS
DN1	A7	WHITE	2	D-
DP1	A6	GREEN	3	D+
GND	A1,B1,A12,B12	BLACK	5	GND
CC	A5			
SHIELD	SHELL	SHIELD	SHELL	SHELL

Part Number Table

Description	Part Number
USB 2.0 Micro B Female to USB C Male Adapter	MC000994

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

