



- Vermason black conductive film is made of virgin low density materials with black conductive compound to achieve high toughness and strength.
- The film is carbon loaded for consistent, non-humidity dependent conductivity.
- R_S 1×10^2 to $< 1 \times 10^5$ ohms per IEC 61340-2-3
- It is resistant to common solvents.
- Typical film thickness is 70 micron (0.07mm).
- The material is printed in yellow and meets the requirements of EN 61340-5-1 and Packaging standard IEC 61340-5-3 including marked with ESD protective symbol.
- Marked with ESD protective symbol
- Supplied in packs, quantity of 100 bags.

Typical Physical Properties

Density	0.855g/cc
Tensile strength at break	22MPa (ISO R527)
Elongation at break	750% (ISO R527)
Storage	Between 5-25° C in dry and ventilated area not subject to extremes of low or high temperatures
Tolerance	+10 / -0mm

Item	Dimensions (W x L)
203531	100mm x 100mm
203536	100mm x 150mm
203556	125mm x 200mm
203576	150mm x 200mm
203581	150mm x 225mm
203601	200mm x 225mm
203606	200mm x 305mm
203620	225mm x 305mm
203645	305mm x 405mm
203675	405mm x 455mm
203700	455mm x 610mm

Unless otherwise noted, tolerance $\pm 10\%$
Specifications and procedures subject to change without notice.



Made in the
United Kingdom

Vermason

Conductive Black Bags

VERMASON
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
203531

DATE:
July 2015