

Meets EN 61340-5-1 tested per ANSI/ESD S1.1



Description

- 2.5mm polyurethane insulation
- Conductor is high strength 7-end duplex tinsel for strength and flexibility
- 1 megohm resistor at 10mm socket end
- 4mm banana plug end does not contain a resistor
- Colour: black
- Dielectric Strength: Cords withstand 1250 volts DC for at least one minute
- Standard cords are marked and date coded



Item	Description
VER-27092	1m Coiled Cord,10mm Socket/4mm Plug + Croc Clip, Black
VER-26182	2m Coiled Cord, 10mm Socket/4mm Plug + Croc Clip, Black

Per CLC/TR 61340-5-2: User guide Wrist Strap clause 4.7.2.6 Summary

- "Wrist straps provide an effective means for maintaining personnel at ground potential or at the same potential as the item(s) being handled. People who are at ground potential or a potential the same as the ESDS they are handling cannot discharge to the ESDS when it is handled or touched.
- Wrist straps usually have a current-limiting resistor, typically 1.0×10^6 ohm, molded into the ground cord near the point where the cord attaches to the cuff. The resistor usually has a working voltage rating of 250 V.
- Wrist straps are sometimes supplied with a 1.0×10^6 ohm resistor molded into both ends of the ground cord when both ends of the cord have the same type snap connector.
- Wrist straps should not be worn by personnel where they could come into contact with voltage over 250 V.
- Wrist strap ground cords should have a quick release connector to the cuff so personnel will not be tied to the workstation.
- Wrist strap bands should be worn comfortably snug around the wrist while making full skin contact.
- Wrist strap ground cords shall be connected to a groundable point or an equipotential bonding point. Do not connect to a snap on a dissipative mat unless it is the groundable point for the mat. Do not clip a wrist strap to the edge of a dissipative mat.
- Wrist straps should be tested on a regular basis with daily testing being recommended."



Made in the
United Kingdom

If not otherwise noted, tolerance $\pm 10\%$
Special manufactured items are not returnable for credit

Vermason

Coiled Cord,10mm Socket/4mm Plug + Croc Clip

VERMASON
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
VER-27092

DATE:
December
2015