

Engineered Polymers

SAFETY DATA SHEET SILITE SEALANT WHITE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SILITE SEALANT WHITE
Product number X0107A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Sealant.

1.3. Details of the supplier of the safety data sheet

Supplier ITW Engineered Polymers
Bay 150
Shannon Industrial Estate
Shannon
Co. Clare

+353 (0)61 471 299
+353 (0)61 471 285
mail@itwep.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Elicitation - EUH208
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36/37/38.

2.2. Label elements

Hazard statements EUH208 Contains 4,5-Dichloro-2-octylisothiazol-3(2H)-one. May produce an allergic reaction.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SILITE SEALANT WHITE

ETHYLTRIACETOXYSILANE	1-5%
CAS number: 17689-77-9	REACH registration number: 01-2119881778-15-0000
Classification Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318	Classification (67/548/EEC or 1999/45/EC) Xn;R22. C;R34. R14.
4,5-Dichloro-2-octylisothiazol-3(2H)-one	<1%
CAS number: 64359-81-5	EC number: 264-843-8
M factor (Acute) = 1	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Acute 1 - H400	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Avoid contact with skin and eyes. Do not breathe vapour.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder. Water.
-------------------------------------	--

5.2. Special hazards arising from the substance or mixture

Specific hazards	Irritating gases or vapours.
-------------------------	------------------------------

SILITE SEALANT WHITE

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Do not breathe vapour.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use only in well-ventilated areas. Keep away from heat, sparks and open flame. Open drum carefully as content may be under pressure. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

SILITE SEALANT WHITE

Hand protection	Wear protective gloves made of the following material: Rubber or plastic.
Other skin and body protection	Wear apron or protective clothing in case of contact.
Hygiene measures	Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	White/off-white.
Odour	Acetic acid.
Initial boiling point and range	>200°C @
Flash point	>150°C CC (Closed cup).
Relative density	1.04 - 1.05 @ @ 25 °C°C
Solubility(ies)	Insoluble in water. Soluble in the following materials: acetone Alcohols.

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Strong oxidising agents.
-------------------	--------------------------

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not available.
---	----------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with oxidising agents.
---------------------------	--------------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Acetic acid. Oxides of the following substances: Carbon. Carbon dioxide (CO ₂). Carbon monoxide (CO).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg)	500,000.0
-------------------------	-----------

SILITE SEALANT WHITE

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 30,000.0

Inhalation	Irritating to respiratory system.
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.
Acute and chronic health hazards	Irritating to skin. Irritating to eyes. May cause respiratory system irritation.
Route of entry	Inhalation Skin absorption Ingestion.

SECTION 12: Ecological Information

Ecotoxicity Avoid release to the environment.

12.1. Toxicity

Toxicity Not considered toxic to fish.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Do not discharge into drains or watercourses or onto the ground.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	08 04 99

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

No information required.

UN No. (IMDG)

SILITE SEALANT WHITE

UN No. (ICAO)

14.2. UN proper shipping name

No information required.

14.3. Transport hazard class(es)

No information required.

ADR/RID class

ADR/RID subsidiary risk

ADR/RID label

IMDG class

IMDG subsidiary risk

ICAO class/division

ICAO subsidiary risk

Transport labels

14.4. Packing group

No information required.

ADR/RID packing group

IMDG packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No information required.

EmS

Emergency Action Code

Hazard Identification Number (ADR/RID)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to No information required.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SILITE SEALANT WHITE

SECTION 16: Other information

Revision date	02/07/2015
Revision	5
Supersedes date	12/05/2014
Risk phrases in full	R36/37/38 Irritating to eyes, respiratory system and skin.
Hazard statements in full	EUH208 Contains 4,5-Dichloro-2-octylisothiazol-3(2H)-one. May produce an allergic reaction. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H331 Toxic if inhaled. H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.