TECHNICAL DATA

Version 6

AT2002 High Specification Flame Retardant Cloth Tape

General Description

A flame retardant polycloth laminate tape coated with a special pressure sensitive adhesive.

Meets the requirements of FAR 25.853, an FAA specification.

- Flame retardant
- Easy tear by hand
- Easy unwind
- Excellent adhesion
- Clean peel up to 4 days at 50°C
- Water resistant finish
- Conformable to awkward shapes
- · Good abrasion resistance
- Non corrosive adhesive



Specification

Certification* to the following standards may be available on request. FAR 25.853.

Technical Details

Typical Values

Thickness 0.23mm

Breaking load 38 N/cm

Elongation 45%

Adhesion

Steel 6.0 N/cm

Self 4.5 N/cm

Flame Retardency Meets FAR 25.853

RoHS compliant Yes

Service Temperature -10°C to +60°C

Application Temperature +10°C to +40°C

Storage Temperature +12°C to +25°C

*Standard charge for certificate: £25.00.

NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.



AFERA

Association des Fabricants Européens de Rubans Auto-Adhésifs.

Adding more to adhesive tape

Advance Tapes International Limited Westmoreland Avenue Thurmaston

Thurmaston Leicester LE4 8PH England Tel. +44 (0)116 251 0191 Fax. +44 (0)116 265 2046 contact@advancetapes.com



www.advancetapes.com