
KEMET Part Number: T322A105K020AT



Capacitor, Tantalum, 1 uF, +/-10% Tol, 20 V



Dimensions (mm)			
Symbol	Dimension	Tolerance	
D	2.41	MAX	
L	6.6	MAX	
F	0.51	+/-0.05	
LL	38.1	+/-6.35	

Packaging Specifications		
Package Kind:	Bulk	
Package Type:	Bag	
Package Quantity:	300	

General Information		
Supplier:	KEMET	
Application:	General Purpose	
Body Type:	Axial	
Lead Type:	Un-insulated Wire	
Termination Type:	Tin (Sn)	
RoHS:	Yes	

Specifications		
Capacitance:	1 uF	
Tolerance:	+/-10%	
Voltage:	20 VDC (85C)	
Voltage:	16 VDC (125C Surge)	
Voltage:	0.2 V (125C Reverse)	
Temperature Range:	-55/+125C	
Resistance/ESR:	10 Ohms (100kHz)	
Leakage Current:	0.5 uA	
Dissipation Factor:	4%	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

