

DCT110HIRK2

Article Number: 115-31100

Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 50/pkg



Download spec sheet

Base Data

Local Order Number	DCT110HIRK2
Type	DCT11
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Provides dual separation between bundles to prevent chaffing and abrasion. • 150 lb. tensile strength ensures enough strength for heavy duty applications. • Straps are releasable for increased serviceability.
Product Description	HellermannTyton's dual clamp ties are designed to provide parallel separation between hoses, wires, cables and tubing, protecting them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of tracks, trailers, and heavy duty equipment. The unique one-piece design features the dual head centered on the strap.
Short Description	Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial)	150.0 lbs
Length L (Imperial)	19.2 "
Length L (Metric)	489.0 mm
Fixation Method	Weld Stud Fixing

Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated

Width W (Imperial)	0.5 "
Width W (Metric)	12.7 mm
Width W2 (Imperial)	0.7 "
Width W2 (Metric)	19.7 mm
Height H (Imperial)	0.8 "
Height H (Metric)	19.1 mm
Bundle Diameter Min. (Imperial)	0.2 "
Bundle Diameter Min. (Metric)	6.4 mm
Bundle Diameter Max. (Imperial)	2.3 "
Bundle Diameter Max. (Metric)	58.0 mm
Mounting Hole Diameter D (Imperial)	0.2 "
Mounting Hole Diameter D (Metric)	6.2 mm
Mounting Hole Diameter D Max.	6.2 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 6.2 mm

Stud Size (Imperial) .25 "

Stud Size (Metric) 6.35 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50

Carton Quantity 500 Pieces

Weight (Metric) 12 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +230°F (-40°C to +110°C)

ROHS Compliant Yes