Product data sheet Characteristics

170ENT11001

Modicon Momentum - Ethernet communication adaptor - 10/100 Mbit/s



Main	
Commercial Status	Commercialised
Range of product	Modicon Momentum automation platform
Product or component type	Ethernet TCP/IP communication adaptor
Communication port protocol	Ethernet TCP/IP
Method of access	Master/Slave Peer to peer
Transmission rate	10/100 Mbit/s
Transmission support medium	Shielded twisted pairs cable

Complementary

BOOTP server to assign IP parameters	
Multidrop, star network	
100BASE-TX	
032 per segment >= 0 with hub or repeater	
1000 m without repeater >= 1000 m with repeater	
IP address user assigned Unique IEEE global address	
Fail safe	
CRC-32	
From I/O base	
CE	
1 LED yellow Ethernet network 10 Mbits/s (100T) 1 LED green module active (RUN) 1 LED green Ethernet network state (ST) 1 LED green Ethernet network 10 Mbits/s (10T)	
1 connector RJ45 for 100BASE-TX	
0.07 kg	
	Multidrop, star network 100BASE-TX 032 per segment >= 0 with hub or repeater 1000 m without repeater >= 1000 m with repeater IP address user assigned Unique IEEE global address Fail safe CRC-32 From I/O base CE 1 LED yellow Ethernet network 10 Mbits/s (100T) 1 LED green module active (RUN) 1 LED green Ethernet network state (ST) 1 LED green Ethernet network 10 Mbits/s (10T) 1 connector RJ45 for 100BASE-TX

Environment

Product certifications	CSA	
	UL	
Standards	CSA	
IP degree of protection	IP20	
Protective treatment	TC	
Resistance to electrostatic discharge	8 kV on air IEC 801-2	
	4 kV contact IEC 801-2	
Resistance to electromagnetic fields	10 V/m 801000 MHz IEC 801-3	
Ambient air temperature for operation	060 °C	
Ambient air temperature for storage	-4085 °C	
Relative humidity	95 % without condensation	
Operating altitude	<= 5000 m	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0925 - Schneider Electric declaration of conformity

