

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Installation component housing, Housing cover, Color: light gray, Width: 17.8 mm



### Why buy this product

- ✓ Conforms to DIN EN 43880
- ▼ Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- ☑ Inflammability class V0 according to UL 94
- ✓ Variety of connection technologies
- Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting

# **Key Commercial Data**

| Packing unit                         | 10 pc           |
|--------------------------------------|-----------------|
| Minimum order quantity               | 10 pc           |
| GTIN                                 | 4 046356 096553 |
| Weight per Piece (excluding packing) | 2.73 g          |
| Custom tariff number                 | 85389099        |
| Country of origin                    | Germany         |
| Product key                          | ACHBAB          |

### Technical data

#### General

| Housing type     | Installation component housing |
|------------------|--------------------------------|
| Housing material | Polycarbonate                  |
| Color            | light gray                     |

#### Ambient conditions

| Ambient temperature (operation) | -40 °C 105 °C (depending on power dissipation) |
|---------------------------------|--|

#### **Dimensions**

| Width | 17.8 mm |
|-------|---------|



# Technical data

## Technical data

| Flammability rating according to UL 94 | V0 |
|--|----|
| Standards and Regulations              |    |
| Flammability rating according to UL 94 | V0 |

## Classifications

# eCl@ss

| eCl@ss 4.0 | 27180401 |
|------------|----------|
| eCl@ss 4.1 | 27180401 |
| eCl@ss 5.0 | 27180506 |
| eCl@ss 5.1 | 27180506 |
| eCl@ss 6.0 | 27180802 |
| eCl@ss 7.0 | 27182702 |
| eCl@ss 8.0 | 27182702 |

#### **ETIM**

| ETIM 2.0 | EC001031 |
|----------|----------|
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC000886 |
| ETIM 5.0 | EC001031 |

## UNSPSC

| UNSPSC 6.01   | 31261501 |
|---------------|----------|
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |

## Approvals

#### Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approvals submitted



## Approvals

Approval details

UL Recognized **\$\)** 

EAC

#### Accessories

Accessories

Fiber optics

Component housing - HS LC-H-D3/ R1XC1 - 2202313



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent

Component housing - HS LC-H-5X2/ R1XC1 - 2202314



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent

Component housing - HS LC-H-D3/ R2XC1-5,08 - 2202315



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent

Component housing - HS LC-H-D2/ R2XC1-2,54 - 2202316



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent



### Accessories

Component housing - HS LC-H-D2/ R2XC2-2,54 - 2202317



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent

Component housing - HS LC-H-D2/ R2XC5-2,54 - 2202318



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent

Component housing - HS LC-H-D2/ R2XC10-2,54 - 2202319



Fiber optics can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed), Color: transparent

Phoenix Contact 2016 @ - all rights reserved http://www.phoenixcontact.com