

Spec Sheet

4-Port USB 3.0 Hub - USB-C to 1x USB-C and 3x USB-A

StarTech ID: HB30C3A1CFB



The 4-port USB 3.0 hub lets you connect both USB-C[™] and USB-A peripherals to your laptop or Chromebook[™], through a single USB Type-C[™] or Thunderbolt[™] 3 port.

The hub is ideal for virtually all USB-C equipped laptops, such as the Dell™ Latitude 11 5000 2-in-1, and the Dell XPS 12.



Get ready for USB-C

This USB 3.1 Gen 1 hub lets you expand your USB connection options using the USB-C port on your computer. It offers one USB-C and three USB-A ports, letting you connect traditional USB devices now, while still being able to connect the growing number of USB Type-C devices in the future.



Spec Sheet

The integrated, easy-to-use USB Type-C connector is small and reversible, which makes for easier insertions. You can connect the plug with either side facing up, which means less risk of damaging your ports, and less frustration.

Add USB ports to your laptop, anywhere you go

With a compact and lightweight design, the USB-powered hub is tailored for mobility. It easily tucks into your carrying case and expands your connectivity when traveling.

Plus, this versatile USB hub takes up minimal space on a desk, so you can use it in hot-desk or BYOD (Bring Your Own Device) environments.

Save money and time

Avoid the nuisance and cost of purchasing new peripherals by using this USB 3.0 hub with your current USB 3.0 and 2.0 devices. The bus-powered hub installs in seconds with no additional drivers or software required, and it's compatible with virtually all operating systems.

The HB30C3A1CFB is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Applications

- Carry the hub with you while traveling, and connect virtually any USB peripheral wherever you go
- Leverage the USB-C port on your BYOD MacBook or laptop to broaden your data connection possibilities
- Deploy in hot desk environments to provide USB hub access for multiple devices

Features

- Expand the connectivity of your USB-C enabled computer using the latest USB 3.1 Gen 1 technology
- Carry the USB-powered hub with you anywhere, with a portable and lightweight design
- Add both USB-C and USB-A ports to your MacBook, Chromebook, or computer that features a USB Type-C port
- Thunderbolt 3 data port compatible
- · Fast, easy installation with broad OS support and no additional drivers required
- Backward compatible with older USB 3.0 and 2.0 devices
- Compliant with USB 3.1 Gen 1 and data rate up to 5Gbps
- Plug-and-play and hot-swap compatible

StarTechcom

Hard-to-find made easy®

Spec Sheet

Technical Specifications

Bus TypeUSB 3.0Chipset IDGenesys Logic - GL 3522Fast-ChargeNoPort(s)SindardsIndustryUSB 3.0 - Backward compatible with USB 2.0 and 1.1StandardsInterfaceInterfaceUSB 3.0InterfaceUSB 3.1 Gen 1Ports4USB-C DeviceYesPort(s)YesUSB-C DeviceYesPort(s)VesUSB-C DeviceYesPort(s)YesUSB-C DeviceYesConnectionS GbpsTransfer RateUSB 3.0 - 5 Gbit/sConnector3 - USB Type-A (9 pin) USB 3.0 FemaleType and RateUSB Type-C (24 pin) USB 3.0 FemaleType(s)-Connector1 - USB Type-C (24 pin) USB 3.0 FemaleType(s)-Connector1 - USB Type-C (24 pin) USB 3.0 FemaleType(s)-Connector1 - USB Type-C (24 pin) USB 3.0 FemaleType(s)-NoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort TM Alt Mode) - non-USB based native video support over the USB Type-C port.NoteNaliable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Available USB Type-C port - USB 3.1 Gen 1 (5Gbps)Cather-Powered-Humidity0%-90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)Timerate-Vertor0°C to 60°C (32°F to 140°F)	Warranty	2 Years
Fast-Charge Port(s)NoIndustryUSB 3.0 - Backward compatible with USB 2.0 and 1.1StandardsUSB 3.0 - Backward compatible with USB 2.0 and 1.1InterfaceUSB 3.0InterfaceUSB 3.1 Gen 1Ports4USB-C DeviceYesPort(s)YesUSB-C HostYesConnectionYesMaximum Data5 GbpsTransfer RateUSB 3.0 - 5 Gbit/sConnector3 - USB Type-A (9 pin) USB 3.0 FemaleType (s)Ypes-C (24 pin) USB 3.0 FemaleConnector1 - USB Type-C (24 pin) USB 3.0 FemaleType(s)0S Independent, No additional drivers or software requiredCompatibilityOS Independent, No additional drivers or software requiredNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and CableKailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%-90% RH (Non-condensing)Operating0°C to 60°C (32°E to 140°F)	Bus Type	USB 3.0
Port(s) USB 3.0 - Backward compatible with USB 2.0 and 1.1 Standards Interface Interface USB 3.0 Interface USB 3.1 Gen 1 Ports 4 USB-C Device Yes Port(s) Yes Connection Yes Maximum Data 5 Gbps Transfer Rate USB 3.0 - 5 Gbit/s Connector 3 - USB Type-A (9 pin) USB 3.0 Female Type (s) So I USB Type-C (24 pin) USB 3.0 Female Connector 1 - USB Type-C (24 pin) USB 3.0 Female Type(s) So Independent; No additional drivers or software required Compatibility OS Independent; No additional drivers or software required Compatibility All ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C opt. Note All ports support DP Alt Mode or USB Power Delivery. System and Auiteures of support DP Alt Mode or USB Power Delivery. System and Auiteures of Support DP Alt Mode or USB Power Delivery. System and Auiteures of Support DP Alt Mode or USB Power Delivery. System and Auiteures of Support DP Alt Mode or USB Power Delivery.	Chipset ID	Genesys Logic - GL3522
Standards Interface USB 3.0 Interface USB 3.1 Gen 1 Ports 4 USB-C Device Yes Port(s)	•	No
InterfaceUSB 3.1 Gen 1Ports4USB-C DeviceYesPort(s)YesUSB-C HostYesConnectionS GbpsTransfer RateGbpsType and RateUSB 3.0 - 5 Gbit/sConnector3 - USB Type-A (9 pin) USB 3.0 FemaleType(s)1 - USB Type-C (24 pin) USB 3.0 FemaleConnector1 - USB Type-C (24 pin) USB 3.0 FemaleType(s)0S Independent; No additional drivers or software requiredOSUSB Type-C (24 pin) USB 3.0 MaleType(s)0S Independent; No additional drivers or software requiredNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort TM Alt Mode) - non-USB based native video support over the USB Type-C port.NoteNatiable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		USB 3.0 - Backward compatible with USB 2.0 and 1.1
Ports4USB-C Device Port(s)YesUSB-C Host ConnectionYesMaximum Dats Transfer RateS GbpsTransfer RateUSB 3.0 - 5 Gbit/sConnector Type and RateUSB 3.0 - 5 Gbit/sConnector Type(s)3 - USB Type-A (9 pin) USB 3.0 Female Type(s)Connector Type(s)1 - USB Type-C (24 pin) USB 3.0 Female Type(s)Connector Type(s)1 - USB Type-C (24 pin) USB 3.0 Female Type(s)OS Connector Type(s)0S Independent; No additional drivers or software requiredNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort TM Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.NoteVailable USB Type-C port - USB 3.1 Gen 1 (5Gbps) Power SourcePower SourceUSB-PoweredHumidity0%~90% RH (Non-condensing) O'C to 60°C (32°F to 140°F)	Interface	USB 3.0
USB-C Device Port(s)YesUSB-C Host ConnectionYesUSB-C Host ConnectionYesMaximum Data5 GbpsTransfer RateS GbpsType and RateUSB 3.0 - 5 Gbit/sConnector Type(s)3 - USB Type-A (9 pin) USB 3.0 FemaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 FemaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 FemaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 MaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 MaleOS Connector Type(s)0 S Independent; No additional drivers or software requiredOS CompatibilityOS Independent; No additional drivers or software requiredNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%-90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)	Interface	USB 3.1 Gen 1
Port(s) Yes USB-C Host Connection Yes Maximum Dats 5 Gbps 5 Gbps Transfer Rate S 3.0 - 5 Gbit/s Connector Type (and Rate USB 3.0 - 5 Gbit/s 3 - USB Type-A (9 pin) USB 3.0 Female Connector Type(s) 1 - USB Type-C (24 pin) USB 3.0 Female Connector Type(s) 1 - USB Type-C (24 pin) USB 3.0 Female Connector Type(s) 1 - USB Type-C (24 pin) USB 3.0 Male Connector Type(s) 1 - USB Type-C (24 pin) USB 3.0 Male OS OS Independent; No additional drivers or software required Compatibility Note Note All ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port. Note The hub does not support DP Alt Mode or USB Power Delivery. System and Cable Available USB Type-C port - USB 3.1 Gen 1 (5Gbps) Power Source USB-Powered Humidity 0%~90% RH (Non-condensing) Operating 0°C to 60°C (32°F to 140°F)	Ports	4
Connection Maximum Data 5 Gbps Transfer Rate S Gbps Type and Rate USB 3.0 - 5 Gbit/s Connector 3 - USB Type-A (9 pin) USB 3.0 Female Type(s) 1 - USB Type-C (24 pin) USB 3.0 Female Connector 1 - USB Type-C (24 pin) USB 3.0 Female Type(s) 1 - USB Type-C (24 pin) USB 3.0 Female Connector 1 - USB Type-C (24 pin) USB 3.0 Male Type(s) 1 - USB Type-C (24 pin) USB 3.0 Male Connector 1 - USB Type-C (24 pin) USB 3.0 Male Type(s) 0 S Independent; No additional drivers or software required Compatibility 0 S Independent; No additional drivers or software required Note All ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port. Note The hub does not support DP Alt Mode or USB Power Delivery. System and Acailable USB Type-C port - USB 3.1 Gen 1 (5Gbps) Sale Cable USB-Powered Fequirements USB-Powered Fower Source USB-Powered Humidity 0%~90% RH (Non-condensing) Operating 0°C to 60°C (32°F to 140°F)		Yes
Transfer RateType and RateUSB 3.0 - 5 Gbit/sConnector3 - USB Type-A (9 pin) USB 3.0 FemaleType(s)1 - USB Type-C (24 pin) USB 3.0 FemaleConnector1 - USB Type-C (24 pin) USB 3.0 MaleType(s)1 - USB Type-C (24 pin) USB 3.0 MaleConnector1 - USB Type-C (24 pin) USB 3.0 MaleType(s)0S Independent; No additional drivers or software requiredOSOS Independent; No additional drivers or software requiredCompatibilityAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and CableAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		Yes
Note3 - USB Type-A (9 pin) USB 3.0 FemaleType(s)1 - USB Type-C (24 pin) USB 3.0 FemaleType(s)1 - USB Type-C (24 pin) USB 3.0 FemaleConnector1 - USB Type-C (24 pin) USB 3.0 MaleType(s)0 SOSOS Independent; No additional drivers or software requiredCompatibilityNoteNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsVSB-PoweredPower SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		5 Gbps
Type(s)1 - USB Type-C (24 pin) USB 3.0 FemaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 MaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 MaleOS CompatibilityOS Independent; No additional drivers or software requiredNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsVSB-PoweredPower SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)	Type and Rate	USB 3.0 - 5 Gbit/s
Type(s)1 - USB Type-C (24 pin) USB 3.0 MaleConnector Type(s)1 - USB Type-C (24 pin) USB 3.0 MaleOSOSOSOS Independent; No additional drivers or software requiredCompatibilityAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		3 - USB Type-A (9 pin) USB 3.0 Female
Type(s)OSOS Independent; No additional drivers or software requiredCompatibilityNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		1 - USB Type-C (24 pin) USB 3.0 Female
CompatibilityNoteAll ports support USB based video adapters including the USB-C port. This hub does not support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		1 - USB Type-C (24 pin) USB 3.0 Male
support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the USB Type-C port.NoteThe hub does not support DP Alt Mode or USB Power Delivery.System and Cable RequirementsAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)Power SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)		OS Independent; No additional drivers or software required
System and CableAvailable USB Type-C port - USB 3.1 Gen 1 (5Gbps)RequirementsPower SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)	Note	support DP Alt Mode (DisplayPort™ Alt Mode) - non-USB based native video support over the
Cable RequirementsPower SourceUSB-PoweredHumidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)	Note	The hub does not support DP Alt Mode or USB Power Delivery.
Humidity0%~90% RH (Non-condensing)Operating0°C to 60°C (32°F to 140°F)	Cable	Available USB Type-C port - USB 3.1 Gen 1 (5Gbps)
Operating 0°C to 60°C (32°F to 140°F)	Power Source	USB-Powered
Operating 0°C to 60°C (32°F to 140°F)	Humidity	0%~90% RH (Non-condensing)
	Operating	



Hard-to-find made easy®

-20°C to 60°C (-4°F to 140°F) Storage Temperature Cable Length 114 mm [4.5 in] Color Black Enclosure Plastic Type Form Factor Compact Product Height 13 mm [0.5 in] Product Length 75 mm [3 in] Product Weight 33 g [1.2 oz] Product Width 40 mm [1.6 in] 96 g [3.4 oz] Shipping (Package) Weight Included in 1 - 4-port USB 3.1 gen 1 hub Package

Certifications, Reports and Compatibility











Spec Sheet