



SAFETY DATA SHEET

Permabond ET500A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond ET500A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-component, epoxy-based adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire. SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone UK +44 (0)1962 711 661 USA 0800 640 7599 Asia +86 (0)21 5773 4913

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified


Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43. N;R51/53.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

PermaBond ET500A

Precautionary statements	P273 Avoid release to the environment. P280 Wear protective gloves, eye and face protection. P302+P352a IF ON SKIN: Wash with plenty of soap and water P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Supplemental label information	EUH205 Contains epoxy constituents. May produce an allergic reaction.
Contains	EPOXY RESIN (Number average MW ≤ 700)
Supplementary precautionary statements	P264 Wash contaminated skin thoroughly after handling. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P501 Dispose of contents/container in accordance with existing Community, National and local regulations.

2.3. Other hazards

None under normal conditions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW ≤ 700)		60-100%
CAS number: 25068-38-6		EC number: 500-033-5
Classification	Classification (67/548/EEC or 1999/45/EC)	
Skin Irrit. 2 - H315	R43 Xi;R36/38 N;R51/53	
Eye Irrit. 2 - H319		
Skin Sens. 1 - H317		
Aquatic Chronic 2 - H411		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. If symptoms develop, obtain medical attention
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any contact lenses and open eyelids wide apart. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	Skin irritation. Mild dermatitis, allergic skin rash.
Eye contact	Irritating and may cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. Treat symptomatically.
-----------------------------	---

PermaBond ET500A

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NO_x). Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal. Wash area with soap and water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

7.3. Specific end use(s)

Specific end use(s) Adhesive. Sealant.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

PermaBond ET500A

Eye/face protection	The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166
Hand protection	Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should not be worn. Gloves should conform to EN 374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
Other skin and body protection	Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.
Hygiene measures	Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Mild.
Odour threshold	Not available.
pH	Not available.
Melting point	Not determined.
Initial boiling point and range	Not applicable.
Flash point	>100°C
Evaporation rate	Not available.
Vapour pressure	Not determined.
Vapour density	Not available.
Relative density	1.17
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not available.
Viscosity	~15000 mPa s @ 23°C
Explosive properties	Not determined.
Oxidising properties	Not determined.

9.2. Other information

Other information	Not relevant.
--------------------------	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Under normal conditions of storage and use, no hazardous reactions will occur.
-------------------	--

PermaBond ET500A

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Reactions with the following materials may generate heat: Amines.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents. Strong acids. Strong alkalis.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects The toxicological properties of this product have not been fully evaluated. Avoid direct contact with skin or eyes. Do not ingest or inhale.

Skin sensitisation

Skin sensitisation May cause sensitisation by skin contact.

Aspiration hazard

Aspiration hazard None under normal conditions.

Inhalation

Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

Ingestion

No harmful effects expected from quantities likely to be ingested by accident.

Skin contact

Irritating to skin.

Eye contact

Irritating and may cause redness and pain.

Toxicological information on ingredients.

EPOXY RESIN (Number average MW <= 700)

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 11,400.0

Species Rat

ATE oral (mg/kg) 11,400.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.1

Species Rabbit

Permabond ET500A

ATE dermal (mg/kg) 2,000.1

SECTION 12: Ecological Information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity No data available.

Ecological information on ingredients.

EPOXY RESIN (Number average MW ≤ 700)

Acute toxicity - fish LC₅₀, 24 hours: 4.4 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates LC₅₀, 24 hours: 4.9 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 48 hours: 9.1 mg/l, Selenastrum capricornutum

Acute toxicity - microorganisms IC₅₀, 3 hours: > 100 mg/l, Activated sludge

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 0.3 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

Ecological information on ingredients.

EPOXY RESIN (Number average MW ≤ 700)

Biodegradation Water - 6 - 12%: 28 days

12.3. Bioaccumulative potential

Ecological information on ingredients.

EPOXY RESIN (Number average MW ≤ 700)

Bioaccumulative potential BCF: 100 - 3000,

Partition coefficient log Pow: 3.242

12.4. Mobility in soil

Mobility No data available. The product has poor water-solubility.

Ecological information on ingredients.

EPOXY RESIN (Number average MW ≤ 700)

Adsorption/desorption coefficient Water and sediment - log K_{oc}: 2.65 @ 20°C

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

PermaBond ET500A

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.
Disposal methods	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Waste class	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

Road transport notes	Applies only to inner containers >5 litres. See SP 375
Sea transport notes	Applies only to inner containers >5 litres. See 2.10.2.7 of the IMDG code.
Air transport notes	Applies only to inner containers >5 litres. See SP A197 (375)

14.1. UN number

3082

UN No. (ADR/RID) 3082


14.2. UN proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains Epoxy resin)

14.3. Transport hazard class(es)

9

Transport labels



14.4. Packing group

III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

PermaBond ET500A

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.
Water hazard classification	WGK 2

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	03/07/2015
Revision	3
Supersedes date	20/05/2015
Risk phrases in full	R36/38 Irritating to eyes and skin. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



SAFETY DATA SHEET

Permabond ET500B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond ET500B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-component, epoxy-based adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Permabond Engineering Adhesives Ltd.
Wessex Way
Colden Common
Winchester
Hampshire. SO21 1WP
United Kingdom
Tel: +44 (0)1962 711 661
Fax: +44 (0)1962 711 662
info.europe@permabond.com

1.4. Emergency telephone number

Emergency telephone UK +44 (0)1962 711 661 USA 0800 640 7599 Asia +86 (0)21 5773 4913

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36/38. R43.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Permabond ET500B

Precautionary statements	<p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P302+P352a IF ON SKIN: Wash with plenty of soap and water</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/attention.</p>
Contains	TRIETHYLENETETRAMINE, PROPOXYLATED, TRIETHYLENETETRAMINE
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with existing Community, National and local regulations.</p>

2.3. Other hazards

None under normal conditions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TRIETHYLENETETRAMINE, PROPOXYLATED		5-10%
CAS number: 26950-63-0		EC number: 500-055-5
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H312	Xn;R21. C;R34. R43,R52/53.	
Skin Corr. 1B - H314		
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
Aquatic Chronic 3 - H412		
TRIETHYLENETETRAMINE		1-5%
CAS number: 112-24-3		EC number: 203-950-6
Classification	Classification (67/548/EEC or 1999/45/EC)	
Acute Tox. 4 - H312	C;R34 Xn;R21 R43 R52/53	
Skin Corr. 1B - H314		
Eye Dam. 1 - H318		
Skin Sens. 1 - H317		
Aquatic Chronic 3 - H412		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. If symptoms develop, obtain medical attention

PermaBond ET500B

Eye contact Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove any contact lenses and open eyelids wide apart. Get medical attention. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Ingestion May cause chemical burns in mouth and throat.

Skin contact Chemical burns. Mild dermatitis, allergic skin rash.

Eye contact May cause serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards No unusual fire or explosion hazards noted.

Hazardous combustion products Burning produces irritating, toxic and obnoxious fumes. Nitrous gases (NOx). Carbon monoxide, carbon dioxide, and unknown hydrocarbons.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Transfer to suitable, labelled containers for disposal. Wash area with soap and water.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

Storage class Corrosive storage.

PermaBond ET500B

7.3. Specific end use(s)

Specific end use(s) Adhesive. Sealant.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal eye protection should conform to EN 166

Hand protection

Nitrile rubber or Viton™ gloves are recommended. Cotton or other absorbent gloves should not be worn. Gloves should conform to EN 374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Employee must wear appropriate protective clothing and equipment to prevent any possibility of skin contact with this substance.

Hygiene measures

Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Use of good industrial hygiene practices is required.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Colourless.
Odour	Amine.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	>100°C
Evaporation rate	Not available.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	1.13
Solubility(ies)	Slightly soluble in water. Soluble in the following materials: Organic solvents.

PermaBond ET500B

Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	~22500 mPa s @ 23°C
Explosive properties	Not determined.
Oxidising properties	Not applicable.

9.2. Other information

Other information	Not relevant.
-------------------	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Under normal conditions of storage and use, no hazardous reactions will occur.
------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Reactions with the following materials may generate heat: Epoxy resin
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Acids. Oxidising agents.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition could produce carbon monoxide, carbon dioxide, and unidentified organic compounds.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	The toxicological properties of this product have not been fully evaluated. Avoid direct contact with skin or eyes. Do not ingest or inhale.
-----------------------	--

Acute toxicity - dermal

Skin sensitisation

Skin sensitisation	May cause sensitisation by skin contact.
--------------------	--

Aspiration hazard

Aspiration hazard	None under normal conditions.
-------------------	-------------------------------

Inhalation

Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature. In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

Ingestion

Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact

This product is strongly irritating. Prolonged contact may cause burns.

Eye contact

Causes serious eye damage.

PermaBond ET500B

Toxicological information on ingredients.

TRIETHYLENETETRAMINE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 2,500.0

Species Rat

ATE oral (mg/kg) 2,500.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 1,465.4

Species Rabbit

ATE dermal (mg/kg) 1,100.0

Reproductive toxicity

Reproductive toxicity - development Developmental toxicity: - NOAEL: 750 mg/kg, , Rat Developmental toxicity: - NOAEL: 125 mg/kg, , Rabbit

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity There are no data on the ecotoxicity of this product.

Ecological information on ingredients.

TRIETHYLENETETRAMINE

Acute toxicity - fish LC₅₀, 96 hours: 330 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 31.1 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 20 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

TRIETHYLENETETRAMINE

Partition coefficient log Pow: -2.65

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

PermaBond ET500B

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste disposal should be in accordance with existing Community, National and local regulations Empty containers may contain product residue; follow SDS and label warnings even after they have been emptied.

Disposal methods Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Waste class 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

14.1. UN number

2735

14.2. UN proper shipping name

POLYAMINES, LIQUID, CORROSIVE, N.O.S (contains Triethylenetetramine)

14.3. Transport hazard class(es)

8

Transport labels



14.4. Packing group

III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-A, S-B

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

PermaBond ET500B

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.
Water hazard classification	WGK 2

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	22/05/2015
Revision	3
Supersedes date	08/05/2014
Risk phrases in full	R21 Harmful in contact with skin. R34 Causes burns. R36/38 Irritating to eyes and skin. R38 Irritating to skin. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Hazard statements in full	H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.