
DPST Push Switch


multicomp


Specifications:

Rating


- : 16A 125/250V AC (UL/CUL)
- 16(4)A 250V ~ T125/55 (VDE/ENEC, CQC) : 1,000V AC 1 minute
- Withstand Voltage Contact Resistance Insulation Resistance Illumination
- : 20mΩ initial (Max.) : 500V DC - 100MΩ (Min.)
- : 100 ~ 125V AC







Dimensions : Inches/Millimetres Tolerances ±0.012"/0.3mm





1	X (Panel Thickness)	Y (Cutout Dimension)	Z (Cutout Dimension)
- z -	0.75mm to 1.25mm	19.2 +0/-0.1mm	
	1.25mm to 2mm	19.4 +0/-0.1mm	12.9 +0.15/-0mm
	2mm to 3mm	19.8 +0/-0.1mm	

Part Number Table

Description	Base Colour	Actuator Colour	Part Number
	Black	Green	MCPS-5-210-PLBG-SC
DPST Push Switch		Orange	MCPS-5-210-PLBO-SC
		Red	MCPS-5-210-PLBR-SC

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

