

Safety Data Sheet

Loctite 3090 Part A

Page 1 of 9

MSDS-No.: 442955 V001.2 Revision: 04.09.2015 printing date: 27.05.2016

Section 1. Identification of the substance/preparation and of the company/undertaking			
Product name:	Loctite 3090 Part A		
Other means of identification: Product code: Recommended use of the chemica	LOCT 3090 PART A IDH1380760 cal and restrictions on use		
Intended use:	Adhesive		
Identification of manufacturer, importer or distributor Importer: Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia. Phone :+ 603 22461000 Fax : + 60322461188			
E-mail address of person responsible for Safety Data Sheet:	ap-ua-psra.sea@henkel.com		
Emergency information:	24 Hours Emergency Tel: +44 (0)1442 278497		

Section 2. Hazards identification

GHS Classification:

Hazard Class Skin corrosion/irritation Serious eye damage/eye irritation	Hazard Category Category 2 Category 2 Category 3
Specific target organ toxicity - single exposure	Category 3

GHS label elements:

Hazard pictogram:

Signal word:



Target organ

respiratory tract irritation

Hazard statement:	H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation.	
Precaution:		
Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray.P264 Wash hands thoroughly after handling.P280 Wear eye protection/face protection.P280 Wear protective gloves.	
Response:	 P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. 	
Storage:	P403+P233 Store in a well-ventilated place. Keep container tightly closed.	
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	

Section 3. Composition / information on ingredients

Substance or Mixture: Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Ethyl 2-cyanoacrylate	60-100%	Skin corrosion/irritation 2
7085-85-0		H315
		Serious eye damage/eye irritation 2
		H319
		Specific target organ toxicity - single exposure 3
		H335
Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane	0.1- 1%	Toxic to reproduction 2
119-47-1		H361f
		Chronic hazards to the aquatic environment 4
		H413
Hydroquinone	< 0.1 %	Acute toxicity 4; Oral
123-31-9		H302
		Serious eye damage/eye irritation 1
		H318
		Skin sensitizer 1
		H317
		Germ cell mutagenicity 2
		H341
		Carcinogenicity 2
		H351
		Acute hazards to the aquatic environment 1
		H400
		Chronic hazards to the aquatic environment 1
		H410

	Section 4. First aid measures			
Inhalation:	Move to fresh air, consult doctor if complaint persists.			
Skin contact:	Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such a spoon, preferably after soaking in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.			
Eye contact:	If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.			
Ingestion:	Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).			
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures			
	Section 5. Fire fighting measures			
Suitable extinguishing media:	Foam, extinguishing powder, carbon dioxide. Fine water spray			
Improper extinguishing media:	None known			
Specific hazards arising from the chemical:	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released In case of fire, keep containers cool with water spray.			
Special protection equipment and precautions for firefighters:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).			
	Oxides of carbon, oxides of nitrogen, irritating organic vapors.			

Section 6. Accidental release measures			
Personal precautions:	Ensure adequate ventilation.		
Environmental precautions:	Do not let product enter drains.		
Clean-up methods:	Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.		

Section 7. Handling and storage

Handling:

Ventilation (low level) is recommended when using large volumes Use of dispensing equipment is recommended to minimise the risk of skin or eye contact Storage:

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

ETHYL CYANOACRYLATE 7085-85-0	Value type	Time Weighted Average (TWA):
	ppm	0.2
	Remarks	ACGIH
ETHYL CYANOACRYLATE 7085-85-0	Value type	Time Weighted Average (TWA):
	ppm	0.2
	Remarks	MY OEL
HYDROQUINONE 123-31-9	Value type	Time Weighted Average (TWA):
	mg/m ³	1
	Remarks	ACGIH
HYDROQUINONE 123-31-9	Value type	Time Weighted Average (TWA):
	mg/m ³	2
	Remarks	MY OEL

Respiratory protection:	Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A	
Hand protection:	 Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced. Polyethylene or polypropylene gloves are recommended when using large volumes. Do not use PVC, rubber or nylon gloves. Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced. 	
Eye protection:	The use of chemical resistant gloves such as Neoprene or Natural Rubber is recommended Wear protective glasses.	
Hygienic measures:	Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while working. Good industrial hygiene practices should be observed.	

colourless

Appearance:

	Liquid
Odor:	Irritating
Odor threshold (CA):	No data available.
pH:	No data available.
Melting point / freezing point:	No data available.
Specific gravity:	No data available.
Boiling point:	No data available.
Flash point:	80 °C (176 °F)80 °C (176 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Solubility:	No data available.
Partition coefficient: n-	No data available.
octanol/water:	
Auto ignition:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

VOC content: (2010/75/EC)

< 3 %

Section 10. Stability and reactivity

Reactivity/Incompatible materials: Chemical stability: Conditions to avoid: Hazardous decomposition products: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols. Stable under recommended storage conditions. Stable under normal conditions of storage and use. None if used for intended purpose.

Section 11. Toxicological information

Symptoms of Overexposure:

EYE: Irritation, conjunctivitis. SKIN: Redness, inflammation. RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Acute oral toxicity:

Ethyl 2-cyanoacrylate 7085-85-0	Value type	LD50
	Value	> 5,000 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)
Bis(2-hydroxy-3-tert-butyl-5-	Value type	LD50
methylphenyl)methane	Value	>10,000 mg/kg
119-47-1	Species	rat
	Method	
Hydroquinone	Value type	LD50
123-31-9	Value	367 mg/kg
	Species	rat
	Method	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

Ethyl 2-cyanoacrylate	Value type	LD50
7085-85-0	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation:

Ethyl 2-cyanoacrylate	Result	slightly irritating
7085-85-0	Exposure time	24 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Ethyl 2-cyanoacrylate	Result	irritating
7085-85-0	Exposure time	72 h
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Ethyl 2-cyanoacrylate	Result	not sensitising
7085-85-0	Test type	
	Species	guinea pig
	Method	
Hydroquinone	Result	sensitising
123-31-9	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	

Germ cell mutagenicity:

Ethyl 2-cyanoacrylate	Result	negative
7085-85-0	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl 2-cyanoacrylate	Result	negative
7085-85-0	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Ethyl 2-cyanoacrylate	Result	negative
7085-85-0	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 473 (In vitro Mammalian Chromosome
		Aberration Test)
Bis(2-hydroxy-3-tert-butyl-5-	Result	negative
methylphenyl)methane	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
119-47-1	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroquinone	Result	negative
123-31-9	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	EU Method B.13/14 (Mutagenicity)

Repeated dose toxicity:

Hydroquinone	Result	NOAEL=>= 250 mg/kg
123-31-9	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 days5 days/week. 12 doses
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral
		Toxicity in Rodents)
Hydroquinone	Result	LOAEL=<= 500 mg/kg
123-31-9	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 days5 days/week. 12 doses
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral
		Toxicity in Rodents)

Section 12. Ecological information

General ecological information:

Biological and Chemical Oxygen Demands (BOD and COD) are insignificant., Do not empty into drains / surface water / ground water.

Toxicity:

Bis(2-hydroxy-3-tert-butyl-5-	Value type	EC 50
methylphenyl)methane	Value	> 10,000 mg/l
119-47-1	Acute Toxicity Study	Bacteria
	Exposure time	3 h
	Species	
	Method	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Hydroquinone	Value type	LC50
123-31-9	Value	0.638 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydroquinone	Value type	EC50
123-31-9	Value	0.134 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydroquinone	Value type	EC50
123-31-9	Value	0.335 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroquinone	Value type	EC 50
123-31-9	Value	0.038 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	DIN 38412, part 27 (Bacterial oxygen consumption test)

Persistence and degradability:

Ethyl 2-cyanoacrylate	Result	
7085-85-0	Route of application	aerobic
	Degradability	57 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Bis(2-hydroxy-3-tert-butyl-5-	Result	under test conditions no biodegradation observed
methylphenyl)methane	Route of application	
119-47-1	Degradability	0 %
	Method	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry
		Test)

Hydroquinone	Result	readily biodegradable
123-31-9	Route of application	aerobic
	Degradability	75 - 81 %
	Method	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed
		Bottle Test)

Bioaccumulative potential / Mobility in soil:

Ethyl 2-cyanoacrylate	LogKow	0.776
7085-85-0	Temperature	22 °C
	Method	EU Method A.8 (Partition Coefficient)
Bis(2-hydroxy-3-tert-butyl-5-	LogKow	6.24
methylphenyl)methane	Temperature	
119-47-1	Method	
Hydroquinone	LogKow	0.59
123-31-9	Temperature	
	Method	EU Method A.8 (Partition Coefficient)

	Section 13. Disposal considerations
<u>Product</u>	
Method of disposal:	Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised landfill or incinerate under controlled conditions. Dispose of in accordance with local and national regulations. Contribution of this product to waste is very insignificant in comparison to article in which it is used
Packaging	
Disposal of uncleaned packages:	After use, tubes, cartons and bottles containing residual product should be disposed of a chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

Section 14. Transport information

Road transport ADR: Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN: Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Class:	9
Packing group:	III
Packaging instructions (passenger):	964
Packaging instructions (cargo):	964
UN no.:	3334
Label:	9
Proper shipping name:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)
Additional Information:	Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

Section 15. Regulatory information

Regulatory Information:	Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous
	Chemicals) Regulations 2013 [P.U.(A) 310/213]
	Industry Code of Practice on Chemicals Classification and Hazard Communication

Global inventory status:

Regulatory list	Notification
TSCA	yes
NDSL	yes
IECSC	yes

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.



Safety Data Sheet

Page 1 of 5

Loctite 3090 part B

MSDS-No. : 337099 V001.2 Revision: 04.09.2015 printing date: 27.05.2016

Section 1. Identification of the substance/preparation and of the company/undertaking		
Product name:	Loctite 3090 part B	
Other means of identification:Loctite 3090 part BProduct code:IDH1285400Recommended use of the chemical and restrictions on use		
Intended use:	Activator	
Identification of manufacturer, importer or distributor Importer: Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia. Phone :+ 603 22461000 Fax : + 60322461188		
E-mail address of person responsible for Safety Data Sheet:	ap-ua-psra.sea@henkel.com	
Emergency information:	24 Hours Emergency Tel: +44 (0)1442 278497	

Section 2. Hazards identification

GHS Classification:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

GHS label elements:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

Section 3. Composition / information on ingredients

Substance or Mixture: Mixture

Declaration of hazardous chemical:

Does not contain ingredients or impurities which contribute to hazard classification.

Section 4. First aid measures

Inhalation:	Should not be a problem as product is of low volatility. However, if feeling unwell remove patient to fresh air.
Skin contact:	Wash skin with water In case of adverse health effects seek medical advice.
Eye contact:	Flush eyes with plenty of water for at least 5 minutes. If irritation persists seek medical attention.
Ingestion:	Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. In case of adverse health effects seek medical advice.
Indication of immediate medical attention and special treatment needed:	See section: Description of first aid measures
	Section 5. Fire fighting measures
Suitable extinguishing media:	Foam, extinguishing powder, carbon dioxide.
Improper extinguishing media:	None known
Special protection equipment and precautions for firefighters:	Wear self-contained breathing apparatus.
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

Section 6. Accidental release measures	
Personal precautions:	Ensure adequate ventilation.
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Section 7. Handling and storage

Handling:	Use only in well-ventilated areas. Gloves and safety glasses should be worn Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.
Storage:	Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

Respiratory protection:	Use only in well-ventilated areas. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A
Hand protection:	Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): nitrile rubber (NBR; >= 0.4 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.
Eye protection:	Wear protective glasses.
Body protection:	Wear suitable protective clothing.
Engineering controls:	Ensure good ventilation/extraction.
Hygienic measures:	Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

Section 9. Physical and chemical properties

Appearance:	Colorless
	Liquid
Odor:	Characteristic
Odor threshold (CA):	No data available.
pH:	No data available.
Melting point / freezing point:	No data available.
Specific gravity:	No data available.
Boiling point:	258 °C (496.4 °F)
Flash point:	160 °C (320 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Lower explosive limit:	No data available.
Upper explosive limit:	No data available.
Vapor pressure:	< 700 mbar
(no method; 50 °C (122 °F))	
Vapor density:	No data available.
Density:	1.15 g/cm3
Solubility:	No data available.
Partition coefficient: n-	No data available.
octanol/water:	
Auto ignition:	No data available.
Decomposition temperature:	No data available.

Viscosity:

No data available.

VOC content: (2010/75/EC)

< 3 %

Section 10. Stability and reactivity

None if used for intended purpose.

Reactivity/Incompatible materials: Chemical stability: Conditions to avoid: Hazardous decomposition products:

Stable under recommended storage conditions. Stable under normal conditions of storage and use. carbon oxides.

Section 11. Toxicological information

Symptoms of Overexposure:

Prolonged or repeated contact may cause eye irritation. Prolonged or repeated contact may cause skin irritation.

Section 12. Ecological information

General ecological information:	Do not empty into drains / surface water /	ground water.
Scherul ecologicul mist mution.	Bo not empty mito drams / surface water /	Bround mater.

Section 13. Disposal considerations

Product Method of disposal: Dispose of in accordance with local and national regulations. Contribution of this product to waste is very insignificant in comparison to article in which it is used Packaging Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated. Disposal must be made according to official regulations.

Section 14. Transport information

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Section 15. Regulatory information

Regulatory Information:	Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous
	Chemicals) Regulations 2013 [P.U.(A) 310/213]
	Industry Code of Practice on Chemicals Classification and Hazard Communication

Global inventory status:

Regulatory list	Notification
EINECS	yes
TSCA	yes
NDSL	yes
ENCS (JP)	yes
IECSC	yes
ISHL (JP)	yes
NZIOC	yes

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.