KPT-238ESD Antistatic





Features

- Antistatic
- · Heat-resist
- · Anti corrosion
- Pressure-sensitive adhesive
- · No remaining adhesive

Specifications

Construction : Substrate material, primer, adhesive Premier coating, Adhesive : American dow corning silicone adhesive

Substrate Material : Polyimide

Specification Table

Item	Specification	Unit
Film Thickness	0.025 ±0.002	mm
Total Thickness	0.065 ±0.004	mm
Adhesion	2.5 - 4.3	N / 25 mm
Tensile Strength	≥ 85	N / 25 mm
Surface Impedance	≥ 109	Ω
Unwinding Voltage	< 50	V
Heat Resistance	280	°C / 5 min
Length	33	M
Width	3 - 500	mm
Colour	Brown	-
Storage, Handling	Storage must be in a dry, non-corrosive and shine environment	
Shelf Life	Shelf life is 1 year from data of manufacture	

Part Number Table

Description	Part Number
Tape, Kapton, ESD, Brown, 9mm × 33M	PPC212
Tape, Kapton, ESD, Brown, 12mm × 33M	PPC213
Tape, Kapton, ESD, Brown, 19mm × 33M	PPC214
Tape, Kapton, ESD, Brown, 25mm × 33M	PPC215

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

