

(1.27 mm) .050"

FTS SERIES

# MICRO LOW PROFILE TERMINAL STRIPS

## SPECIFICATIONS


For complete specifications and recommended PCB layouts see [www.samtec.com?FTS](http://www.samtec.com?FTS)

### HI-TEMP

**Insulator Material:**  
Black Liquid Crystal Polymer  
**Terminal Material:**  
Phosphor Bronze  
**Operating Temp Range:**  
-55°C to +125°C  
**Plating:**  
Sn or Au over 50µ" (1.27 µm) Ni  
**Current Rating:**  
3.3 A per pin (1 pin powered per row)  
**RoHS Compliant:**  
Yes  
**Lead-Free Solderable:**  
Yes  
**SMT Lead Coplanarity:**  
.004" (0.10 mm) max

Mates with:  
FFSD, CLP, FLE

## OPTIONS



Mates with socket strips or IDC cable

Surface mount or through-hole

Micro pitch .050" x .050" (1.27 mm x 1.27 mm)

Low profile (1.27 mm) .050"

Shrouded and alignment pin options available

Impedance matched for high speed applications

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



## ALSO AVAILABLE (MOQ Required)

- Alignment pin
- Contact Samtec.

FTS	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OTHER OPTION								
		02 thru 50 (except -S & -SA option = 05 thru 46)	<p><b>-01</b> = .120" (3.05 mm) Post (Mates with FFSD)</p> <p><b>-02</b> = .075" (1.91 mm) Post (Mates with FLE)</p> <p><b>-03</b> = .065" (1.65 mm) Post (Mates with CLP)</p>	<p><b>-F</b> = Gold flash on post, Matte Tin on tail</p> <p><b>-L</b> = 10µ" (0.25 µm) Gold on post, Matte Tin on tail</p>	<p><b>-D</b> = Double Through-hole</p> <p><b>-DV</b> = Double Vertical SMT</p> <p><b>-S</b> = Single Through-hole</p> <p><b>-SV</b> = Single Vertical SMT</p>	<p>(-D &amp; -DV only)</p> <p><b>-SA</b> = End Shroud with Alignment Pin (05 thru 46 positions. Style -02 &amp; -03 only)</p> <p><b>-S</b> = End Shroud (05 thru 46 positions. Style -02 &amp; -03 only)</p> <p><b>-P</b> = Pick &amp; Place Pad (04 positions minimum)</p> <p><b>-TR</b> = Tape &amp; Reel (-DV only) (Required callout for positions 2 thru 4)</p>								
			<table border="1"> <thead> <tr> <th>LEAD STYLE</th> <th>A</th> </tr> </thead> <tbody> <tr> <td>-01</td> <td>(3.05) .120</td> </tr> <tr> <td>-02</td> <td>(1.91) .075</td> </tr> <tr> <td>-03</td> <td>(1.65) .065</td> </tr> </tbody> </table>	LEAD STYLE	A	-01	(3.05) .120	-02	(1.91) .075	-03	(1.65) .065			
LEAD STYLE	A													
-01	(3.05) .120													
-02	(1.91) .075													
-03	(1.65) .065													

**Note:** Some lengths, styles and options are non-standard, non-returnable.