

LP1SK0600JD

TeSys SK - mini contactor - 2P (2 NO) - AC-1 - 690 V 12 A - 12 V DC coil



Main

Product or component type	Mini contactor
Device short name	LP1SK
Contactor application	Resistive load
Utilisation category	AC-1
Poles description	2P
Pole contact composition	2 NO
[Ue] rated operational voltage	690 V AC 50/60 Hz for power circuit
[Ie] rated operational current	12 A (<= 55 °C) AC AC-1
Control circuit type	DC standard
Control circuit voltage	12 V DC
[Ith] conventional free air thermal current	12 A at <= 55 °C for power circuit
Irms rated making capacity	66 A at 690 V AC conforming to IEC 60947 66 A at 690 V AC conforming to NF C 63-110
Rated breaking capacity	52 A at <= 400 V for power circuit conforming to NF C 63-110 52 A at <= 400 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	50 A <= 55 °C power circuit
Associated fuse rating	16 A gI at <= 440 V for power circuit conforming to IEC 60947
Average impedance	4 mOhm at 50 Hz - Ith 12 A
[Ui] rated insulation voltage	690 V conforming to BS 5424 690 V conforming to IEC 60947 690 V conforming to VDE 0110 group C 690 V conforming to UL 508 690 V conforming to CSA C22.2 No 14
Mounting support	Rail
Standards	BS 5424 IEC 60947 NF C 63-110 VDE 0660
Product certifications	CSA UL
Connections - terminals	Power circuit : connector 1 cable(s) 0.35...6 mm ² - cable stiffness: flexible - with cable end Power circuit : connector 1 cable(s) 0.5...6 mm ² - cable stiffness: flexible - without cable end Power circuit : connector 1 cable(s) 1.5...6 mm ² - cable stiffness: solid Power circuit : connector 2 cable(s) 0.35...1.5 mm ² - cable stiffness: flexible - with cable end Power circuit : connector 2 cable(s) 0.35...2.5 mm ² - cable stiffness: flexible - without cable end Power circuit : connector 2 cable(s) 1.5...4 mm ² - cable stiffness: solid
Tightening torque	0.8 N.m - on connector - with screwdriver pozidriv No 1
Operating time	4...6 ms coil de-energisation and NO opening 8...12 ms coil energisation and NO closing
Mechanical durability	10 Mcycles
Operating rate	1200 cyc/h

Complementary

Control circuit voltage limits 0.85...1.1 U_c at <= 50 °C operational

0.1...0.75 Uc at <= 50 °C drop-out

Inrush power in W	2.2 W at 20 °C
Hold-in power consumption in W	2.2 W at 20 °C
Heat dissipation	2.2 W

Environment

IP degree of protection	IP2x conforming to VDE 0106
protective treatment	TC conforming to IEC 60068 TC conforming to DIN 50015
ambient air temperature for operation	-20...50 °C
ambient air temperature for storage	-50...70 °C
operating altitude	2000 m without derating in temperature
height	56 mm
width	27 mm
depth	55.5 mm
product weight	0.132 kg

Contractual warranty

Warranty period	18 months
-----------------	-----------