CG100 Digital Coaxial, LSOH Cable Pro-POWER



RoHS Compliant


Characteristics:

Item	Description	Standard
Conductor Resistance	20°C, Conductor DC Resistance	<2.6Ω/100M
Min. Insulation DC Resistance	20°C, Insulation DC Resistance	200MΩ × M
Rated Voltage	-	300V
Rated Temperature	-	80°C
Impedance (Ω) at 200MHz	-	75 ±5Ω
Capacitance (pF/m)	-	53.5 (±5) (pF/m)
Attenuation at 20°C (-dB/100m) (±15%)	55MHZ	5.5
	100MHZ	7.1
	211MHZ	10
	400MHZ	13.68
	870MHZ	20.73
	1000MHZ	22.35
	1750MHZ	31.7
	2150MHZ	35.35
Return Loss	5-30MHZ	>23 dB
	30-470MHZ	>23 dB
	470-862 MHZ	>20dB
	862-2150MHZ	>18dB

Standards:

As per UL1581 & UL444

Cable Construction:



	Material	Copper Covered Steel (26%)		
1. Conductor	Nom.O.D.(mm)	1 × 1	Up	+0.002
			Down	-0.018
	Material	FPE		
2. Insulation	Diameter	4.6 (±0.2)mm		
	Colour	White		
3. Shield	Material	Copper covered aluminium-Foil Shield		
	Colour	Yellow		
4. Braid	Material	Copper Covered Aluminium		
	Nom.O.D.(mm)		0.12 × 64	

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



CG100 Digital Coaxial, LSOH Cable Pro-Power

	Extemal O.D.	6.5 (±0.25)mm		
5. Jacket	Surface	Clean, Smooth		
	Material	LSZH		
	Colour	Black & White		

Part Number Table

Description	Part Number
CG100 Digital Coaxial LSOH, Cable Black, 100m	CG100 BLK 100M LSOH
CG100 Digital Coaxial LSOH, Cable, White, 100m	CG100 WHT 100M LSOH

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

