Multicore Screened Cable

: Bare Copper (OFC) : 10 × 0.11mm : 0.1mm² × 2

pro-**Power**



RoHS Compliant

Specifications:


Cross Section	
Construction	
Material	

Chieldine:	
Colour	: 1) White; 2) Red
Diameter	: 0.85mm × 2C
Thickness	: 0.22mm
Material	: Polyvinylchloride (PVC)

Shielding

Material Construction Coverage	: Bare Copper (OFC) : 43 × 0.1mm Spiral : 97%
Out Jacket	
Material	: Polyvinylchloride (PVC)
Thickness	: 0.45mm
Diameter	: 2.8mm
Operation Temperature Resistance Conductor	: -20°C to +70°C : 199.5Ω/kM

Construction:



Part Number Table

Description	Part Number
Audio Connecting Cable 2 Core, 100m	JY-1060

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the gossibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell pic 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

