

DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DOW CORNING(R) 3140 RTV COATING
Product code : 000000000001981820, 000000000001981820

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Adhesive, binding agents, Electrical industry and electronics

1.3 Details of the supplier of the safety data sheet

Company : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe

Telephone : English Tel: +49 611237507
Deutsch Tel: +49 611237500
Français Tel: +32 64511149
Italiano Tel: +32 64511170
Español Tel: +32 64511163

E-mail address of person responsible for the SDS : sdseu@dowcorning.com

1.4 Emergency telephone number

Dow Corning (Barry U.K. 24h) Tél: +44 1446732350
Dow Corning (Wiesbaden 24h) Tél: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

|| Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

|| Not a hazardous substance or mixture.

||| Precautionary statements : **Prevention:**
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.

Hazardous components which must be listed on the label:

||| Methyltrimethoxysilane

Additional Labelling:

DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

||| EUH210 Safety data sheet available on request.
||| EUH208 Contains Methyltrimethoxysilane. May produce an allergic reaction.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Silicone elastomer

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Methyltrimethoxysilane	1185-55-3 214-685-0 01-2119517436-40	Flam. Liq. 2; H225 Skin Sens. 1B; H317	>= 1 - < 10

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

||| If inhaled : If inhaled, remove to fresh air.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

||| If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

||| Risks : May produce an allergic reaction.



DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Silicon oxides
Formaldehyde
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

DOW CORNING(R) 3140 RTV COATING

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2016
2.0	05.02.2016	1308184-00006	Date of first issue: 10.02.2015

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapour or mist.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Strong oxidizing agents

7.3 Specific end use(s)

Specific use(s) : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may re-

DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

quire added precautions.
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methyltrimethoxysilane	1185-55-3	TWA	7.5 ppm	DCC OEL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	200 ppm 266 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	250 ppm 333 mg/m3	GB EH40
Further information	Can be absorbed through skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Methyltrimethoxysilane	Workers	Skin contact	Acute systemic effects	0.38 mg/kg bw/day
	Workers	Inhalation	Acute systemic effects	25.6 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.38 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	25.6 mg/m3
	Consumers	Skin contact	Acute systemic effects	0.3 mg/kg bw/day
	Consumers	Inhalation	Acute systemic effects	6.25 mg/m3
	Consumers	Ingestion	Long-term systemic	0.26 mg/kg



DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
 Date of first issue: 10.02.2015

			effects	bw/day
	Consumers	Skin contact	Long-term systemic effects	0.3 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	6.25 mg/m3
	Consumers	Ingestion	Acute systemic effects	0.26 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Methyltrimethoxysilane	Fresh water	>= 1.3 mg/l
	Marine water	>= 0.13 mg/l
	Fresh water sediment	>= 1.1 mg/kg
	Marine sediment	>= 0.11 mg/kg
	Soil	>= 0.17 mg/kg
	Sewage treatment plant	> 6.9 mg/l

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
 Ensure adequate ventilation, especially in confined areas.
 Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
 Safety glasses

Hand protection
 Material : Impervious gloves

Remarks : For prolonged or repeated contact use protective gloves.
 Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that

DOW CORNING(R) 3140 RTV COATING

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2016
2.0	05.02.2016	1308184-00006	Date of first issue: 10.02.2015

exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: white, translucent
Odour	: slight
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 65 °C
Flash point	: > 101.1 °C Method: closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: 1.05
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: 300 Poise
Explosive properties	: Not explosive



DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.
Can react with strong oxidizing agents.
When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released.
Adequate ventilation is required.
Hazardous decomposition products will be formed upon contact with water or humid air.
Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

Contact with water or humid air : Methanol
Thermal decomposition : Formaldehyde

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

Acute toxicity

|| Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Components:

Methyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat): 12.3 ml/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity : LC50 (Rat): > 42.1 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on test data

Acute dermal toxicity : LD50 (Rabbit): > 9,500 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on test data

Skin corrosion/irritation

|| Not classified based on available information.

Components:

Methyltrimethoxysilane:

Species: Rabbit
Result: No skin irritation
Remarks: Based on test data

Serious eye damage/eye irritation

|| Not classified based on available information.

Components:

Methyltrimethoxysilane:

Species: Rabbit
Result: No eye irritation
Remarks: Based on test data



DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

||

Respiratory or skin sensitisation

|| Skin sensitisation: Not classified based on available information.
|| Respiratory sensitisation: Not classified based on available information.

Product:

|| Assessment: Does not cause skin sensitisation.
|| Test Type: Buehler Test
|| Species: Guinea pig
|| Remarks: Based on data from similar materials

Components:

Methyltrimethoxysilane:

|| Assessment: Probability or evidence of low to moderate skin sensitisation rate in humans
|| Test Type: Buehler Test
|| Species: Guinea pig
|| Remarks: Based on test data

Germ cell mutagenicity

|| Not classified based on available information.

Components:

Methyltrimethoxysilane:

|| Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
|| Result: negative
|| Remarks: Based on test data
|| : Test Type: Mutagenicity (in vitro mammalian cytogenetic test)
|| Result: positive
|| Remarks: Based on test data
|| : Test Type: Chromosome aberration test in vitro
|| Result: positive
|| Remarks: Based on test data
|| Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
|| cytogenetic assay)
|| Species: Mouse
|| Application Route: Ingestion
|| Result: negative
|| Remarks: Based on test data
|| Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

|| Not classified based on available information.

Reproductive toxicity

|| Not classified based on available information.



DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

Components:

Methyltrimethoxysilane:

- Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat, male and female
Application Route: Ingestion
Symptoms: No effects on fertility
Remarks: Based on test data
- Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat, male and female
Application Route: Ingestion
Symptoms: No effects on foetal development
Remarks: Based on test data
- Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT - single exposure

|| Not classified based on available information.

STOT - repeated exposure

|| Not classified based on available information.

Components:

Methyltrimethoxysilane:

- Exposure routes: inhalation (vapour)
Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.
- Exposure routes: Ingestion
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

Methyltrimethoxysilane:

- Species: Rat
Application Route: inhalation (vapour)
Remarks: Based on test data
- Species: Rat
Application Route: Ingestion
Remarks: Based on test data

Aspiration toxicity

|| Not classified based on available information.

Product:

No aspiration toxicity classification

DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

SECTION 12: Ecological information

12.1 Toxicity

Components:

Methyltrimethoxysilane:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp.): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 3.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility EC10 (Pseudokirchneriella subcapitata (green algae)): > 3.6 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: No toxicity at the limit of solubility
Toxicity to bacteria	: EC50 : > 100 mg/l Method: OECD Test Guideline 209

12.2 Persistence and degradability

Components:

Methyltrimethoxysilane:

Stability in water	: Degradation half life: 2.2 h pH: 7
--------------------	--------------------------------------

12.3 Bioaccumulative potential

Components:

Methyltrimethoxysilane:

Partition coefficient: n-octanol/water	: log Pow: -2.36
--	------------------

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available



DOW CORNING(R) 3140 RTV COATING

Version 2.0 Revision Date: 05.02.2016 SDS Number: 1308184-00006 Date of last issue: 06.01.2016
Date of first issue: 10.02.2015

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

DOW CORNING(R) 3140 RTV COATING

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2016
2.0	05.02.2016	1308184-00006	Date of first issue: 10.02.2015

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Other regulations : Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.

KECI : All ingredients listed, exempt or notified.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

TCSI : All ingredients listed or exempt.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H317 : May cause an allergic skin reaction.

Full text of other abbreviations

Flam. Liq. : Flammable liquids
Skin Sens. : Skin sensitisation
2006/15/EC : Europe. Indicative occupational exposure limit values

DOW CORNING(R) 3140 RTV COATING

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2016
2.0	05.02.2016	1308184-00006	Date of first issue: 10.02.2015

DCC OEL	: Dow Corning Guide
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2006/15/EC / TWA	: Limit Value - eight hours
DCC OEL / TWA	: Time weighted average
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet	: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
---	---

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provid-

DOW CORNING(R) 3140 RTV COATING

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2016
2.0	05.02.2016	1308184-00006	Date of first issue: 10.02.2015

ed relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN