

TYPE MCR-001 Programm Terminal Block

PUSH-BUTTON PRESSING



Case length	60 mm (2.361 in)
Case width	25 mm (0.984 in) (including 2.5 mm (0.098 in) of case)
Case height	12 mm (0.472 in) (including 2.5 mm (0.098 in) of case)
Case depth	12 mm (0.472 in)

Operating temperature	-25° to +55° C (-13° to +131° F)
Max. storage temperature	-40° to 80° C (-40° to 176° F)

Current rating	16 Amp (AC/DC)
Insulation resistance min.	100,000,000 Ohm
Insulation resistance	100,000,000 Ohm
Withstand voltage	500 V AC
Withstand voltage	50 V DC
Mounting screws	2.5 x 6 mm



PUSH-BUTTON PRESSING

Term. No.	Push	Current	Capacity
MCR-001-0001	0	0 A DC	0.001
MCR-001-0002	0	16 A DC	0.001
MCR-001-0003	0	16 A DC	0.001
MCR-001-0004	0	16 A DC	0.001
MCR-001-0005	0	16 A DC	0.001
MCR-001-0006	0	16 A DC	0.001
MCR-001-0007	0	16 A DC	0.001
MCR-001-0008	0	16 A DC	0.001
MCR-001-0009	0	16 A DC	0.001
MCR-001-0010	0	16 A DC	0.001
MCR-001-0011	0	16 A DC	0.001
MCR-001-0012	0	16 A DC	0.001