
Spec Sheet

SMD Power Inductors (NR series S type)

NRS5020T100MMGJ



Features

- Item Summary
 10uH±20%, 1.3A, 4.9x4.9x2.0mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 800pcs


■ Products characteristics table

Inductance	10 uH ± 20 %
Case Size (mm)	4.9x4.9
Rated Current (max)	1.3 A
Saturation Current (max)	1.3 A
Temperature Rise Current (max)	1.45 A
DC Resistance (typ)	0.12 Ω
DC Resistance (max)	0.144 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	24 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	4.9 ±0.2 mm
Dimension W	4.9 ±0.2 mm
Dimension H	Max 2.0 mm
Dimension e	1.2 ±0.2 mm

Recommended Land Patterns



2016.01.25

TAIYO YUDE

SMD Power Inductors (NR series S type)

NRS5020T100MMGJ



Dimension unit : mm unit: inch Length: 4.9 + / - 0.2(0.193 + / - 0.008)Width: 4.9 +/- 0.2 (0.193 + / - 0.008)Height: 2.0 max. (0.079 max.)

Inductance: 10 (test freq at 0.1MHz) иΗ DC Resistance: 0.12 / 0.144 ohm (typ/max)

Saturation Current: 1,300 mA (max) 1,450 mA (max) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

