
Spec Sheet

SMD Power Inductors (NR series S type)

NRS6010T2R2MMGF



Features

- Item Summary 2.2uH±20%, 1.7A, 6.0x6.0x1.0mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 1000pcs


Products characteristics table

Inductance	2.2 uH ± 20 %
Case Size (mm)	6.0x6.0
Rated Current (max)	1.7 A
Saturation Current (max)	1.9 A
Temperature Rise Current (max)	1.7 A
DC Resistance (typ)	0.11 Ω
DC Resistance (max)	0.132 Ω
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	56 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

■ External Dimensions

Dimension L	6.0 ±0.2 mm
Dimension W	6.0 ±0.2 mm
Dimension H	Max 1.0 mm
Dimension e	1.35 ±0.2 mm

Recommended Land Patterns



2016.01.25

SMD Power Inductors (NR series S type)

NRS6010T2R2MMGF



Dimension unit : mm unit: inch Length: 6.0 + / - 0.2(0.236 + / - 0.008)Width: 6.0 + / - 0.2(0.236 +/- 0.008) max.) Height: 1.0 (0.039 max.

Inductance: 2.2 иΗ (test freq at 0.1MHz) DC Resistance: 0.11 / 0.132 ohm (typ/max)

Saturation Current: 1,900 mA (max) 1,700 mA (max) Temp. rise Current:

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

