
Spec Sheet

SMD Power Inductors (NS series)

NS10145T330MNA



Features

- Item Summary 33uH±20%, 2.01A, 10.1x10.1x4.5mm
- Lifecycle Stage
 Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 2000pcs(500pcs*4reel)


Products characteristics table

Inductance	33 uH ± 20 %
Case Size (mm)	10.1x10.1
Rated Current (max)	2.01 A
Saturation Current (max)	2.36 A
Temperature Rise Current (max)	2.01 A
DC Resistance (typ)	81.5 mΩ
DC Resistance (max)	97.8 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	10.5 MHz
Operating Temp. Range	-40 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	10.1 ±0.3 mm
Dimension W	10.1 ±0.3 mm
Dimension H	4.5 ±0.35 mm


Recommended Land Patterns



2016.01.25

SMD Power Inductors (NS series)

NS10145T330MNA



Dimension unit: mm unit: inch

Length: 10.1 +/- 0.3 (0.398 +/- 0.012)

Width: 10.1 +/- 0.3 (0.398 +/- 0.012)

Height: 4.5 +/- 0.35 (0.177 +/- 0.014)

Inductance: 33 uH (test freq at 0.1MHz)
DC Resistance: 0.0815 / 0.0978 ohm (typ / max)

Saturation Current: 2.36 A (max) Temp. rise Current: 2.01 A (max)

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

