
Spec Sheet

SMD Power Inductors (NS series)

NS10165T150MNA



Features

- Item Summary 15uH±20%, 3.84A, 10.1x10.1x6.5mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 2000pcs(500pcs*4reel)

Products characteristics table

Inductance	15 uH ± 20 %
Case Size (mm)	10.1x10.1
Rated Current (max)	3.84 A
Saturation Current (max)	4.5 A
Temperature Rise Current (max)	3.84 A
DC Resistance (typ)	25 mΩ
DC Resistance (max)	30 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	13.2 MHz
Operating Temp. Range	-40 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	10.1 ±0.3 mm
Dimension W	10.1 ±0.3 mm
Dimension H	6.5 ±0.35 mm

Recommended Land Patterns




2.5

2.5

2016.01.25

SMD Power Inductors (NS series)

NS10165T150MNA



Dimension unit: mm unit: inch

Length: 10.1 + /- 0.3 (0.398 +/- 0.012)

Width: 10.1 +/- 0.3 (0.398 +/- 0.012)

Height: 6.5 +/- 0.35 (0.256 +/- 0.014)

Inductance: 15 uH (test freq at 0.1MHz)
DC Resistance: 0.025 / 0.03 ohm (typ/max)

Saturation Current: 4.50 A (max) Temp. rise Current: 3.84 A (max)

Saturation current typical: 30% reduction from initial L value.

Temp rise Current typical: Temperature will rise by 40 deg C

