
Spec Sheet

SMD Power Inductors (NR series S type)

NRS8030T100MJGJ



Features

- Item Summary 10uH±20%, 2.4A, 8.0x8.0x3.0mm
- Lifecycle Stage
 - Mass Production
- Standard packaging quantity (minimum)
 Taping Embossed 1000pcs


■ Products characteristics table

Inductance	10 uH ± 20 %
Case Size (mm)	8.0x8.0
Rated Current (max)	2.4 A
Saturation Current (max)	2.4 A
Temperature Rise Current (max)	3 A
DC Resistance (typ)	33 mΩ
DC Resistance (max)	42.9 mΩ
LQ Measuring Frequency	100 kHz
Self Resonant Frequency (min)	27 MHz
Operating Temp. Range	-25 to +125 ℃ (Including-self-generated heat)
RoHS2 Compliance	Yes
REACH Compliance	Yes
Soldering	Reflow

External Dimensions

Dimension L	8.0 ±0.2 mm
Dimension W	8.0 ±0.2 mm
Dimension H	Max 3.0 mm
Dimension e	1.6 ±0.3 mm

Recommended Land Patterns



2016.01.25

SMD Power Inductors (NR series S type)

NRS8030T100MJGJ



Dimension unit : mm unit: inch Length: 8.0 + / - 0.2(0.315 + / - 0.008)Width: 8.0 +/- 0.2 (0.315 + / - 0.008)max.) Height: 3.0 max. (0.118

Inductance: 10 иΗ (test freq at 0.1MHz) DC Resistance: 0.033 / 0.0429 ohm (typ/max)

Saturation Current: 2,400 mA (max) Temp. rise Current: 3,000 mA (max)

> Saturation current typical: 30% reduction from initial L value. Temp rise Current typical: Temperature will rise by 40 deg C

