

Spec Sheet

#### DisplayPort to HDMI Adapter Cable - 3 m (10 ft.) - 4K 30Hz

StarTech ID: DP2HDMM3MB



This 3-meter (10 ft.) DisplayPort to HDMI® adapter cable lets you connect your DisplayPort equipped Ultrabook<sup>™</sup>, laptop or desktop computer to an HDMI television, monitor or projector, with no additional adapters or cables required. The passive adapter supports video resolutions up to Ultra HD 4K, ensuring support for high-resolution applications.

## Astonishing picture quality

This adapter cable ensures you can maintain an astonishing 4K picture quality, four times the resolution of 1080p, when converting DisplayPort to HDMI. The adapter is also backward-compatible with lower-resolution displays and video sources. With support for high-definition resolutions of 1080p and 720p, you can future-proof your existing setup for 4K video.

## Hassle-free setup

For the simplest and most discreet installation, this DP to HDMI adapter connects directly from your DisplayPort video source to the HDMI port on your display. It doesn't need a power source, unlike some converter dongles that require active power and separate bulky video cabling.

## **Clutter-free installation**

With a built-in DP to HDMI adapter, this 3 m cable delivers a direct connection that eliminates the need for additional adapters, ensuring a tidy, professional installation. Plus, because the cable is 3 meters (10 feet) in length, the cable is ideal when connecting your computer to a display that's further away than a standard 6 ft. (2 m) cable.

For shorter or longer installations, we also offer a <u>1 m DP to HDMI cable (DP2HDMM1MB</u>), a <u>2 m DP to HDMI cable (DP2HDMM2MB</u>) and a <u>{5 m DP to HDMI cable (DP2HDMM5MB</u>) enabling you to choose the right cable length for your custom installation needs.

www.startech.com 1 800 265 1844



Spec Sheet

The DP2HDMM3MB is backed by a 2-year StarTech.com warranty and free lifetime technical support.

#### Applications

- Connect a DisplayPort computer to an HDMI display at your classroom desk or workstation
- Use in your boardroom or office workstations for installations requiring 3 m (10 ft.) of cable
- Install in your home workstation to make your DisplayPort computer compatible with your HDMI display
- Connect your DP video source to a 4K HDMI display

#### Features

- Astonishing video quality with support for resolutions up to 4K at 30 Hz
- Reduce clutter with a compact 3 m (10 ft.) adapter cable
- Avoid the hassle of converters that require additional cabling and power adapters, with a plug-and-play cable adapter
- Supports HDMI 4K @ 30 Hz
- Plug-and-play installation
- No power adapter required



Hard-to-find made easy®

# Spec Sheet

#### **Technical Specifications**

Adapter StyleAdapterAudioYesConverter TypePassiveIndustry StandardsDPCP (DisplayPort Content Protection) HDCP (High Definition Content Protection) DisplayPort 1.2 HDMI 1.4Ports1Audio Specifications7.1 surround soundMaximum Digital Resolutions4K x 2K @ 30 HzSupported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Warranty	2 Years
Converter TypePassiveIndustry StandardsDPCP (DisplayPort Content Protection) HDCP (High Definition Content Protection) DisplayPort 1.2 HDMI 1.4Ports1Audio Specifications7.1 surround soundMaximum Digital Resolutions4K x 2K @ 30 HzSupported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Adapter Style	Adapter
Industry StandardsDPCP (DisplayPort Content Protection) HDCP (High Definition Content Protection) DisplayPort 1.2 HDMI 1.4Ports1Audio Specifications7.1 surround soundMaximum Digital Resolutions4K x 2K @ 30 HzSupported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperatureo°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Audio	Yes
HDCP (High Definition Content Protection) DisplayPort 1.2 HDMI 1.4Ports1Audio Specifications7.1 surround soundMaximum Digital Resolutions4K x 2K @ 30 HzSupported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Converter Type	Passive
Audio Specifications7.1 surround soundMaximum Digital Resolutions4K x 2K @ 30 HzSupported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Industry Standards	HDCP (High Definition Content Protection) DisplayPort 1.2
Maximum Digital Resolutions4K x 2K @ 30 HzSupported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Ports	1
Supported Resolutions4k x 2K (Ultra HD) 1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F) -10°C to 70°C (14°F to 158°F)	Audio Specifications	7.1 surround sound
1920x1200 1920x1080 (1080p) 1280x720 (720p)Wide Screen SupportedYesConnector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Maximum Digital Resolutions	4K x 2K @ 30 Hz
Connector A1 - DisplayPort (20 pin) Male InputConnector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Supported Resolutions	1920x1200 1920x1080 (1080p)
Connector B1 - HDMI (19 pin) Male OutputHumidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Wide Screen Supported	Yes
Humidity10%-85%Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Connector A	1 - DisplayPort (20 pin) Male Input
Operating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 70°C (14°F to 158°F)	Connector B	1 - HDMI (19 pin) Male Output
Storage Temperature -10°C to 70°C (14°F to 158°F)	Humidity	10%-85%
	Operating Temperature	0°C to 70°C (32°F to 158°F)
Color Black	Storage Temperature	-10°C to 70°C (14°F to 158°F)
	Color	Black
Product Length 9.8 ft [3 m]	Product Length	9.8 ft [3 m]
Product Weight 4.4 oz [124 g]	Product Weight	
Shipping (Package) Weight 0.3 lb [0.1 kg]	Shipping (Package) Weight	0.3 lb [0.1 kg]
Included in Package 1 - DisplayPort to HDMI cable	Included in Package	1 - DisplayPort to HDMI cable



## Hard-to-find made easy®

**Certifications, Reports and Compatibility** 















Spec Sheet

www.startech.com 1 800 265 1844