SAFETY DATA SHEET



1. Identification of the substance/preparation and of the company/undertaking

Product name	Castrol Tection 15W-40
SDS #	454756
Product Use	Automotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult your Castrol representative.
Supplier	Castrol (UK) Ltd. Witan Gate House 500-600 Witan Gate Central Milton Keynes MK9 1ES United Kingdom
EMERGENCY TELEPHONE NUMBER	+44 (0) 1908 853000

2. Composition/information on ingredients

Highly refined mineral oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Chemical name	CAS no.	%	EINECS / ELINCS.	Classification
phosphorodithioc acid, O,O - di- C1-14- alkyl esters zinc salts	68649-42-3	1 - 5	272-028-3	Xi; R38, 41 N; R51/53
See Section 16 for the full text of the R Phrases declared above				
Occupational Exposure Limit(s), if available, are listed in Section 8				

3. Hazards identification

This preparation is not classified as dangerous according to Directive 1999/45/EC as amended and adapted.

	3
Physical/chemical Hazards	Not classified as dangerous.
Human health hazards	Not classified as dangerous.
Environmental hazards	Unlikely to be harmful to aquatic organisms.
Effects and symptoms	
Eyes	No significant health hazards identified.
Skin	No significant health hazards identified.
	USED ENGINE OILS Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.
Inhalation	No significant health hazards identified.
Ingestion	No significant health hazards identified.

4. First-aid measures

Eye Contact	In case of contact, immediately flush eyes with a copious amount of water for at least 15 minutes. Get medical attention if irritation occurs.
Skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.

Product Name Ca	astrol Tection 15W-40	Product Code	454756-GB01	Page: 1/4
Version 2	Date of issue 3 July 2003	Format United Kingdom (UK)	Language	
		(BUILD 5.1.2)	(E	NGLISH)

5. Fire-fighting measures

Extinguishing Media	
Suitable	In case of fire, use water fog, foam, dry chemical or CO2 extinguisher or spray.
Not Suitable	Do not use water jet.
Hazardous decomposition products	These products are carbon oxides (CO, CO2), phosphates. Some metallic oxides.
Unusual fire/explosion Hazards	None.
Special fire-fighting procedures	None identified.
Protection of fire-fighters	Fire fighters should wear self-contained positive pressure breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal Precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Follow all fire fighting procedures (Section 5).
Environmental precautions and cleanup methods	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Minimize contact of spilled material with soils to prevent runoff to surface waterways. See Section 13 for Waste Disposal Information.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves.

7. Handling and storage

Handling	Wash thoroughly after handling.		
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area.		

8. Exposure controls/personal protection

Occupational Exposure Limits	None assigned.
Control Measures	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location.
Hygiene measures	Wash hands after handling compounds and before eating, smoking, using lavatory, and at the end of day.
Personal protective equipment	
Respiratory system	None required; however, use of adequate ventilation is good industrial practice.
Skin and body	None required; however, use of protective clothing is good industrial practice.
Hands	None required; however, use of gloves is good industrial practice.
Eyes	Safety glasses with side shields.

9. Physical and chemical properties

Flash point	224 °C (OPEN CUP) Cleveland.	
Colour	Amber.	
Odour	Oily	
Odour threshold	Not available.	
Physical state	Liquid.	
Density	881 kg/m³ (0.9 g/cm³) at 15°C	
Solubility	insoluble in water.	
Viscosity	kinematic: 107.8 mm²/s (107.8 cSt) at 40°C kinematic: 14.4 mm²/s (14.4 cSt) at 100°C	

10. Stability and reactivity

Incompatibility with Various Substances	Reactive with oxidizing agents.
Hazardous Polymerization	Will not occur.

Product Name Castrol Tection 15W-40		Product Code	454756-GB01	Page: 2/4
Version 2	Date of issue 3 July 2003	Format United Kingdom (UK)	Language	
		(BUILD 5.1.2)	(6	ENGLISH)

11. Toxicological information

Acute toxicity	Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
	Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis.
	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
	Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
	At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Chronic toxicity	
Carcinogenic effects	No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH, the International Agency for Research on Cancer (IARC) or the European Commission (EC).

12. Ecological information

Persistence/degradability	Inherently biodegradable	
Mobility	Spillages may penetrate the soil causing ground water contamination.	
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.	
Environmental hazards	Unlikely to be harmful to aquatic organisms.	
Other Ecological Information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.	

13. Disposal considerations

Disposal Consideration / Waste	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste
information	disposal contractor in accordance with local regulations.

14. Transport information

Not classified as hazardous for transport (ADR, RID, UN , IMO, IATA/ICAO).

15. Regulatory information

Label Requirements			
Risk Phrases	This product is not classified according to the EU regulations.		
EU Regulations	Classification and labelling have been performed according to EU directives 1999/45/EC and 67/548/EE as amended and adapted.		
Other Regulations			
Inventories	AUSTRALIAN INVENTORY (AICS): In compliance.		
	CANADA INVENTORY (DSL): In compliance.		
	CHINA INVENTORY (IECS): Not determined.		
	EC INVENTORY (EINECS): In compliance.		
	JAPAN INVENTORY (ENCS): In compliance.		
	KOREA INVENTORY (ECL): In compliance.		
	PHILIPPINE INVENTORY (PICCS): In compliance.		
	US INVENTORY (TSCA): In compliance.		
Additional Warning Phrases	Safety data sheet available for professional user on request.		

Product Name Castrol Tection 15W-40		Product Code	454756-GB01	Page: 3/4
Version 2	Date of issue 3 July 2003	Format United Kingdom (UK)	Language	
		(BUILD 5.1.2)	(E	NGLISH)

16. Other information

Full text of R-phrases appearing	R38- Irritating to skin.
in section 2	R41- Risk of serious damage to eyes.
	R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HISTORY

Date of issue Date of previous issue Prepared by <u>Notice to Reader</u> 03/07/2003. 13/11/2002. Product Stewardship Group

The data and advice given apply when the product is sold for the stated application or applications. The product is not sold as suitable for any other application. Use of the product for applications other than as stated in this sheet may give rise to risks not mentioned in this sheet. You should not use the product other than for the stated application or applications without seeking advice from us.

If you have purchased the product for supply to a third party for use at work, it is your duty to take all necessary steps to secure that any person handling or using the product is provided with the information in this sheet.

If you are an employer, it is your duty to tell your employees and others who may be affected of any hazards described in this sheet and of any precautions which should be taken.

Further copies of this Safety Data Sheet may be obtained from Castrol International.

Product Name Ca	strol Tection 15W-40	Product Code	454756-GB01	Page: 4/4
Version 2	Date of issue 3 July 2003	Format United Kingdom (UK)	Language	
		(BUILD 5.1.2)	(6	ENGLISH)