RMSTR®NG 1/2" Drive 6 Point Metric Deep Impact Sockets

- Made in the USA Quality and Availability
- Radius Corner Design Engages the Flats of the Fastener, Not the Corners, Providing Up to 15%-20% More Torque While Reducing Fastener Rounding, Enhancing the Turning of Worn Fasteners
- EYE-DTM Markings Optimize Size Visibility, Also Providing SAE / Metric Differentiation
- Socket Wall Dimensions Are Optimized to Provide Strength While Retaining Access to Restricted Fasteners
- Manufactured From High Alloy Steel Using the Most Up-To-Date Manufacturing Process and Heat Treat for Greater Strength and Durability
- Meets or Exceeds ASME B107.33M-2002







Cat. No.	UPC No.	Packaging	Fastener Size	Dim. A: Drive End	Dim. B: Wrench End	Dim. C: Overall Length	Dim. D: Bolt Clearance	Dim. E: Wrench Depth	Dim. F: Length to Shoulder	Product Weight	Shelf Pack Qty.
47-208	781412472080	Bagged	8 mm	0.874 in	0.512 in	3.228 in	0.205 in	0.374 in	0.492 in	0.49 lb	1
47-209	781412472097	Bagged	9 mm	0.874 in	0.614 in	3.228 in	0.220 in	0.437 in	0.492 in	0.36 lb	1
47-210D	781412472103	Bagged	10 mm	0.878 in	0.614 in	3.228 in	0.374 in	0.571 in	0.492 in	0.38 lb	1
47-211	781412472110	Bagged	11 mm	0.878 in	0.657 in	3.228 in	0.425 in	0.571 in	0.492 in	3.24 lb	1
47-212	781412472127	Bagged	12 mm	0.878 in	0.740 in	3.228 in	0.449 in	0.571 in	0.492 in	3.26 lb	1
47-213	781412472134	Bagged	13 mm	0.961 in	0.791 in	3.228 in	0.492 in	0.500 in	0.492 in	3.27 lb	1
47-214	781412472141	Bagged	14 mm	0.961 in	0.874 in	3.228 in	0.543 in	0.500 in	0.492 in	0.44 lb	1
47-215D	781412472158	Bagged	15 mm	0.961 in	0.961 in	3.228 in	0.583 in	0.500 in	=	0.42 lb	1
47-216	781412472165	Bagged	16 mm	0.961 in	0.961 in	3.228 in	0.614 in	0.531 in	-	0.39 lb	1
47-217	781412472172	Bagged	17 mm	1.047 in	1.047 in	3.228 in	0.650 in	0.531 in	-	0.48 lb	1
47-218	781412472189	Bagged	18 mm	1.094 in	1.094 in	3.228 in	0.669 in	0.571 in	-	0.54 lb	1
47-219	781412472196	Bagged	19 mm	1.185 in	1.185 in	3.228 in	0.709 in	0.630 in	-	0.66 lb	1
47-220	781412472202	Bagged	20 mm	1.252 in	1.252 in	3.228 in	0.748 in	0.630 in	-	0.67 lb	1
47-221	781412472219	Bagged	21 mm	1.252 in	1.252 in	3.228 in	0.748 in	0.630 in	-	0.72 lb	1
47-222	781412472226	Bagged	22 mm	1.260 in	1.260 in	3.228 in	0.748 in	0.669 in	-	0.72 lb	1
47-223	781412472233	Bagged	23 mm	1.311 in	1.311 in	3.228 in	0.787 in	0.689 in	-	0.81 lb	1
47-224	781412472240	Bagged	24 mm	1.311 in	1.311 in	3.228 in	0.787 in	0.689 in	-	0.74 lb	1
47-225	781412472257	Bagged	25 mm	1.437 in	1.437 in	3.268 in	0.752 in	0.689 in	=	0.96 lb	1
47-226	781412472264	Bagged	26 mm	1.500 in	1.500 in	3.268 in	0.752 in	0.780 in	-	0.96 lb	1
47-227	781412472271	Bagged	27 mm	1.500 in	1.500 in	3.268 in	0.815 in	1.496 in	=	1.00 lb	1
47-228	781412472288	Bagged	28 mm	1.563 in	1.563 in	3.500 in	0.815 in	0.874 in	-	1.01 lb	1
47-229	781412472295	Bagged	29 mm	1.626 in	1.626 in	3.500 in	1.063 in	1.098 in	-	1.02 lb	1
47-230	781412472301	Bagged	30 mm	1.626 in	1.626 in	3.500 in	1.063 in	1.098 in	-	1.14 lb	1
47-232	781412472325	Bagged	32 mm	1.752 in	1.752 in	3.500 in	1.118 in	1.126 in	-	1.20 lb	1
47-234	781412472349	Bagged	34 mm	2.000 in	2.000 in	3.500 in	1.299 in	1.350 in	-	1.25 lb	1
47-235	781412472356	Bagged	35 mm	2.000 in	2.000 in	3.500 in	1.299 in	1.350 in	-	1.29 lb	1
47-236	781412472363	Bagged	36 mm	2.000 in	2.000 in	3.500 in	1.299 in	1.350 in	-	1.30 lb	1