
KEMET Part Number: C927U332MYVDBA7317



Capacitor, ceramic, 3300 pF, +/-20% Tol, 400 V, Y5V, Lead Spacing=7.5 mm



| Dimensions (mm) | | | |
|-----------------|-----------|-----------|--|
| Symbol | Dimension | Tolerance | |
| D | 9 | MAX | |
| Т | 5 | MAX | |
| S | 7.5 | +/-1 | |
| LL | 18 | +2/-0 | |
| F | 0.5 | +/-0.1 | |

| Packaging Specifications | | |
|--------------------------|------|--|
| Package Kind: | Ammo | |
| Package Quantity: | 1000 | |

| General Information | | |
|--------------------------|--------------|--|
| Supplier: | KEMET | |
| Application: | Safety:X1/Y2 | |
| Temperature Coefficient: | Y5V | |
| Body Type: | Radial Disc | |
| Lead Form: | vcrimp | |
| Termination Type: | Tin (Sn) | |
| RoHS: | Yes | |
| Halogen Free: | Yes | |

| Specifications | | |
|------------------------|-------------|--|
| Capacitance: | 3300 pF | |
| Voltage: | 400 VAC (X) | |
| Voltage: | 250 VAC (Y) | |
| Tolerance: | +/-20% | |
| Temperature Range: | -40/+125C | |
| Failure Rate: | N/A | |
| Dissipation Factor: | 5% | |
| Insulation Resistance: | 10 GOhm | |
| Dielectric Strength: | 2600 V | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

