KEMET Part Number: T110D107K020AT

Electronic Components KEMET CHARGED.

Capacitor, Tantalum, 100 uF, +/-10% Tol, 20 V

General Information	
Supplier:	KEMET
Application:	General Purpose
Body Type:	Axial Hermetic
Lead Type:	Un-insulated Wire
Termination Type:	Tin (Sn)
RoHS:	Yes

Specifications	
Capacitance:	100 uF
Tolerance:	+/-10%
Voltage:	20 VDC (85C)
Voltage:	16 VDC (125C Surge)
Voltage:	0.2 V (125C Reverse)
Temperature Range:	-55/+125C
Resistance/ESR:	0.6 Ohms (100kHz)
Leakage Current:	10 uA
Dissipation Factor:	6%

Dimensions (mm)		
Symbol	**Dimension**	**Tolerance**
D	8.92	+/-0.25
L	19.96	+/-0.79
L2	23.42	
F	0.64	+/-0.05
LL	38.1	+/-6.35

Notes:
-When Supplied On T&R Or Ammo, Lead Length Is Determined By Taping Specification

Packaging Specifications	
Package Kind:	Bulk
Package Type:	Tray
Package Quantity:	20

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

IntelliData

© 2006-2016 IntelliData.net