
## KEMET Part Number: C330C224K1R5TA

(C330C224K1R5TABULK)



Capacitor, ceramic, 0.22 uF, +/-10% Tol, 100 V, X7R, Lead Spacing=0.2"



	Temperature Coefficient:	X7R
	Body Type:	Radial Conformal
	Lead Type:	Wire Leads
ane     †	Termination Type:	Tin (Sn)
[	RoHS:	Yes
Specifications		eations
	Specifi	

Dimensions (mm)			
Symbol	Dimension	Tolerance	
L	7.11	MAX	
Н	9.14	MAX	
T	4.07	MAX	
S	5.08	NOM	
LL	7	MIN	
F	0.51	NOM	

Specifications		
Capacitance:	0.22 uF	
Voltage:	100 V	
Tolerance:	+/-10%	
Temperature Range:	-55/+125C	
Failure Rate:	N/A	
Dissipation Factor:	2.5%	
Insulation Resistance:	4.55 GOhm	
Dielectric Strength:	250 V	

**General Information** 

**KEMET** 

General Purpose

Supplier:

Application:

Packaging Specifications			
Package Kind:	Bulk		
Package Type:	Bag		
Package Quantity:	250		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

