


Capacitor, aluminum, 270 uF, +/-20% Tol, -40/+85C, 550 VDC@85C



Dimensions (mm)		
Symbol	Dimension	Tolerance
D	35	+1
L	50	+/-2
S	10	+/-0.1
LL	6.3	+/-1
F	2	+/-0.1

Notes:
 -Dimensions D And L Include Sleevng

General Information	
Supplier:	KEMET
Application:	General Purpose
Part Type Description:	Snap-In, Aluminum Electrolytic
Lead Type:	2 Pin
RoHS:	Yes

Specifications	
Capacitance:	270 uF
Voltage:	550 VDC
Tolerance:	+/-20%
Voltage:	605 VDC (Surge)
Rated Temperature:	85C
Temperature Range:	-40/+85C
Life:	15000 Hrs (Rated Voltage And Ripple Current At 85C)
Life:	24000 Hrs (Rated Voltgae At 85C)
Leakage Current:	891 uA
Leakage Condition:	uAmps (5min 20C)
Resistance/ESR:	1290 mOhms (100Hz 20C)
Resistance/ESR:	1126 mOhms (10kHz 20C)
Current/Ripple Current:	2.01 Amps (100Hz 85C)
Current/Ripple Current:	3.15 Amps (10kHz 85C)

Packaging Specifications	
Package Kind:	Bulk

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.