


Capacitor, aluminum, 1500 uF, +/-20% Tol, -40/+85C, 550 VDC@85C



Dimensions (mm)		
Symbol	Dimension	Tolerance
D	66	+/-1
L	115	+/-2
LT	119	+/-1
S	28.5	+/-0.5
T	5.5	+/-0.5
TD	10	MIN
DT	13	+/-0.5
V	15.8	NOM
Z	10	NOM

Notes:

- Dimensions D And L Include Sleaving
- MS (MxH) = M12x16

General Information	
Supplier:	KEMET
Application:	General Purpose
Part Type Description:	High Voltage Screw Terminal Aluminum Electrolytic
Style:	Screw Terminal
Lead Type:	Threaded Inserts- M6
Weight:	540 g
RoHS:	Yes

Specifications	
Capacitance:	1500 uF
Voltage:	550 VDC
Tolerance:	+/-20%
Voltage:	605 VDC (Surge)
Rated Temperature:	85C
Temperature Range:	-40/+85C
Life:	19000 Hrs
Leakage Current:	4.95 mA
Leakage Condition:	uAmps (5min 20C)
Resistance/ESR:	203.85 mOhms (100Hz 20C)
Resistance/ESR:	180.6 mOhms (10kHz 20C)
Current/Ripple Current:	8.97 Amps (100Hz 85C)
Current/Ripple Current:	14.08 Amps (10kHz 85C)

Packaging Specifications	
Package Kind:	Bulk