
KEMET Part Number: C941U332MVVDBA7317



Capacitor, ceramic, 3300 pF, +/-20% Tol, 400 V, Y5V, Lead Spacing=10 mm



Supplier:	KEMET
Application:	Safety:X1/Y1
Temperature Coefficient:	Y5V
Body Type:	Radial Disc
Lead Form:	vcrimp
Termination Type:	Tin (Sn)
RoHS:	Yes
Halogen Free:	Yes

General Information

Dimensions (mm)			
Symbol	Dimension	Tolerance	
D	11	MAX	
Т	5	MAX	
S	10	+/-1	
LL	18	+2/-0	
F	0.5	+/-0.1	

Specifications		
Capacitance:	3300 pF	
Voltage:	400 VAC (X)	
Voltage:	250 VAC (Y)	
Tolerance:	+/-20%	
Temperature Range:	-25/+125C	
Failure Rate:	N/A	
Dissipation Factor:	5%	
Insulation Resistance:	10 GOhm	
Dielectric Strength:	4000 V	

Packaging Specifications		
Package Kind:	Ammo	
Package Quantity:	1000	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

