

8-bit PIC® Microcontrollers for Motor Control

Precision Control with Integrated Feedback

Summary

Designers of motor control applications constantly face the challenge of increasing efficiency and control, while reducing system cost and components. Finding a balance within these constraints can be accomplished by employing preferred techniques such as Peak Current Mode Control (PCMC). To optimize the efficiency of any system, precise control over switch timing and maintaining constant feedback is crucial. Using a PIC MCU with switch drive capability and feedback components integrated into one chip can help you simplify your system design and reduce costs.


Levels of Motor Control

Within the motor control market, there are different levels of integration and intelligence. Each increase provides more precision and control as well as system efficiency. The most commonly used levels are described below:

- **Level 1:** Limited intelligence is required; the MCU is used for basic control and supervisory functions. The controller handles on/off control, temperature monitoring, automatic shutdown and watchdog fault detection.
- **Level 2:** This level of integration utilizes an MCU with PWMs for motor drive and to interface with analog components for feedback control. The controller is now able to adjust the motor speed depending on application needs, overcurrent or thermal shutdown conditions. Communication can be found in remote applications for improved system control. Advanced systems may require special features to ensure safe motor operation in accordance with government regulations.
- **Level 3:** The last level adds increased intelligence for improved efficiency. The controller provides control over motor waveforms and commutation, which allows the use of advanced algorithms to optimize control and efficiency. Increased system flexibility is needed to reconfigure control loops on the fly as needed for the application.

8-bit PIC MCUs for Motor Control

Products within the 8-bit PIC MCU families offer performance up to 16 MIPS, with many different options that can handle each level of integration. Core Independent Peripherals (CIP) optimized for controlling 1/2 bridge, H-bridge and 3 phase motors, coupled with Intelligent Analog for Peak Current Mode Control (PCMC) and software PID controller creation, as well as communication peripherals, provide the integration needed to reduce system cost while increasing efficiency and control. From the simplicity of the PIC10F family to the hardware multiplier of the PIC18F, the 8-bit PIC MCU product line has the right solution for your system design.



Integrated Peripherals

Intelligent Analog and Control

- Math Accelerator (MathACC)
 - Multiply, add and accumulate 8-/16-bit values with 35-bit results
 - Calculates a 16-bit PID function based on configurable K_p , K_i and K_d constants with a 34-bit result
- Hardware Multiplier (MULT)
 - Multiply 8-bit values with 16-bit resolution
- Angular Timer (AngTMR)
 - Phase angle timer for measurement and control of rotational and periodic events
- Zero Cross Detect (ZCD)
 - AC high-voltage zero crossing detection for simplifying TRIAC control, synchronized switching control and timing
- 24-bit Signal Measurement Timer (SMT)
 - Accurate measurement of any digital signal including period, duty cycle, time of flight and instantaneous vs. average measurements
 - General-purpose 24-bit timer/counter
- Hardware Limit Timer (HLT)
 - Hardware monitoring for missed periodic events and fault detection
 - General-purpose 8-bit timer/counter with external reset capabilities
- Configurable Logic Cell (CLC)
 - Integrated combinational and sequential logic
 - Custom interconnection and re-routing of digital peripherals
- Operational Amplifier (OPA)
 - General purpose op amp for internal and external signal source conditioning
- High Speed Comparator (HSComp)
 - General purpose rail-to-rail comparator with < 50 ns response time



MICROCHIP

Integrated Peripherals (Continued)

Intelligent Analog and Control (Continued)

- Digital to Analog Converter (DAC)
 - Programmable voltage reference with multiple internal and external connections
- Analog to Digital Converter (ADC)
 - General purpose 8-/10-/12-bit ADC with stable voltage reference

Signal Generation

- Programmable Switch Mode Controller (PSMC)
 - 16-bit PWMs with dedicated 64 MHz clock
 - Automated complementary output with programmable rising/falling edge events, auto shutdown, polarity, phase, deadband and blanking control
 - General-purpose 16-bit timer/counter
- 16-bit PWM
 - 16-bit PWM with edge and center aligned modes
 - General-purpose 16-bit timer/counter

- Pulse Width Modulation (PWM)
 - General-purpose 10-bit PWM
- (Enhanced) Capture Compare PWM (CCP/ECCP)
 - 10-bit PWM control with 16-bit capture, compare and auto shutdown
- Complementary Output Generator (COG)
 - Automated complementary output with programmable rising/falling edge events, auto shutdown, polarity, phase, precision deadband and blanking control
- Complementary Waveform Generator (CWG)
 - Automated complementary output with auto shutdown and deadband control
- Numerically Controlled Oscillator (NCO)
 - Precision linear frequency generator (PWM @ 50% duty cycle) with 0.0001% step size of source input clock frequency
 - General-purpose 20-bit timer/counter

Select 8-bit MCUs for Motor Control

Device	Program Memory (B)	SRAM (B)	EEPROM	I/O Pins	A/D (Ch) 8/10/12b	Op Amp	MathACC/MULT	AngTMR	DAC 5/8/9b	Comparator	CCP/ECCP	PWM	PSMC	NCO	COG/CWG	CLC	HLT	SMT	I ² C/SPI	EUSART
PIC10F322	896	64	–	4	3/0/0	–	–	–	–	–	–	1	–	1	0/1	1	–	–	–	–
PIC12F1572	3.5K	256	HEF*	6	0/4/0	–	–	–	1/0/0	1	–	3	–	–	0/1	–	–	–	–	1
PIC12F1612	3.5K	256	HEF*	6	0/4/0	–	–	–	0/1/0	1	2/0	–	–	–	0/1	–	3	2	–	–
PIC16F1615	14K	1K	HEF*	12	0/8/0	–	1/0	1	0/1/0	2	2/0	2	–	–	0/1	4	3	2	1	1
PIC16F1829	14K	1K	256	18	0/12/0	–	–	–	1/0/0	2	2/2	–	–	–	–	–	–	–	1	1
PIC16F1709	14K	1K	HEF*	18	0/12/0	2	–	–	0/1/0	2	2/0	2	–	–	1/0	3	–	–	1	1
PIC16F1619	14K	1K	HEF*	18	0/12/0	–	1/0	1	0/1/0	2	2/0	2	–	–	0/1	4	4	2	1	1
PIC18F24K22	16K	512	256	18	0/12/0	–	0/1	–	–	2	0/1	–	–	–	–	–	–	–	1	1
PIC16F1789	28K	2K	256	36	0/0/14	3	–	–	3/1/0	4	3/0	–	4	–	–	–	–	–	1	1

*HEF = 128B of High-Endurance Flash

Development Tools

- PICkit™ 3 In-Circuit Debugger (PG164130)
- MPLAB® ICD 3 In-Circuit Debugger (DV164035)
- PICDEM™ Lab Development Kit (DM163045)
- MPLAB PM3 Universal Device Programmer (DV007004)
- MPLAB Starter Kit for PIC18F MCU (DM180021)
- PICDEM PIC18 Explorer Board (DM183032)
- F1 LV Evaluation Platform (DM164130-5)
- F1 BLCD Motor Add-On (DM164130-2)
- F1 BDC Motor Add-On (DM164130-6)
- F1 Bipolar Motor Add-On (DM164130-7)
- F1 Unipolar Motor Add-On (DM164130-8)



MICROCHIP

www.microchip.com/8bit

Visit our web site for additional product information and to locate your local sales office.

Microchip Technology Inc. • 2355 W. Chandler Blvd. • Chandler, AZ 85224-6199

Microcontrollers • Digital Signal Controllers • Analog • Memory • Wireless