Part Number: 0934447131

Status: Active

Overview: ML-XT™ Sealed Connection System

Description: ML-XT™ Sealed 18 Circuit Receptacle Housing, Pre-Assembled with Small Rear Seal and Cover, Keying Option C, Black

Series image - Reference only

Documents:

Drawing (PDF)
Application Specification 934430010 (PDF)
Packaging Specification 934430002 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	Crimp Housings
Series	93444
Application	Power, Signal, Wire-to-Wire
Overview	ML-XT™ Sealed Connection System
Product Name	ML-XT™
UPC	889056335348

Physical

Circuits (maximum)	18
Color - Resin	Black
Gender	Receptacle
Glow-Wire Compliant	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	17.440/g
Number of Rows	3
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	N/A
Polarized to Mating Part	Yes
Temperature Range - Operating	-55°C to +125°C

Electrical

Current - Maximum per Contact	13.0A

Material Info

Reference - Drawing Numbers

Application Specification	934430010
Packaging Specification	934430002
Sales Drawing	934430070

EU ELV
Not Reviewed

EU RoHS
Not Reviewed

China RoHS

REACH SVHC
Not Reviewed

Halogen-Free Status
Not Reviewed

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the Contact Us section for any non-product compliance questions.

China ROHS	Not Reviewed
ELV	Not Reviewed

Search Parts in this Series
93444 Series

Mates With
ML-XT™ Sealed 18 Circuit Plug Housing 93445-7131

Use With
ML-XT™ Male (Pin) Terminal 84524-0004 (Nickel), ML-XT™ Male (Pin) Terminal 84524-0014 (Selective Gold)