

5 Watt Metal Film Fixed Resistors



RoHS
Compliant




Performance Specification

- Self extinguishing
- Excellent flame and moisture resistance
- Extremely small sturdy and mechanical safe
- Product Type: Power Film Resistor
- Power Rating: 5 Watts
- Resistance Tolerance: $\pm 5\%$

Performance Specification


Temperature coefficient	: $<20\Omega$: $\pm 400\text{PPM}/^\circ\text{C}$; ≥ 20 : $\pm 350\text{PPM}/^\circ\text{C}$
Short-time overload	: $\Delta R/R < \pm(5.0\% + 0.05\Omega)$, with no evidence of mechanical damage.
Dielectric withstanding voltage	: No evidence of flashover, mechanical damage, arcing or insulation breakdown.
Terminal strength	: No evidence of mechanical damage.
Solderability	: Min. 95% coverage
Temperature cycling	: $\Delta R/R \leq \pm(2.0\% + 0.05\Omega)$, with no evidence of mechanical damage.
Humidity (Steady State)	: $\Delta R/R \leq \pm(5.0\% + 0.05\Omega)$, with no evidence of mechanical damage.
Load life in humidity	: For Wire-wound range, the $\Delta R/R$ is $\pm 5\%$ For Power film range, $<100\text{k}\Omega$, the $\Delta R/R$ is $\pm 5\%$ For Power film range, $\geq 100\text{k}\Omega$, the $\Delta R/R$ is $\pm 10\%$
Load Life	: For Wire-wound range, the $\Delta R/R$ is $\pm 5\%$ For Power film range, $<100\text{k}\Omega$, the $\Delta R/R$ is $\pm 5\%$ For Power film range, $\geq 100\text{k}\Omega$, the $\Delta R/R$ is $\pm 10\%$
Resistance to solderability heat	: $\Delta R/R \pm(1.0\% + 0.05\Omega)$ with no evidence of mechanical damage.

Diagram




Dimensions : Millimetres

Derating Curve



Heat Rise Chart



www.element14.com
www.farnell.com
www.newark.com



5 Watt Metal Film Fixed Resistors



Part Number Table

Description	Part Number
Metal Film Resistor, 1k Ω , 5W, 5%, Radial Lead	MCPRM05WJP102B00
Metal Film Resistor, 10k Ω , 5W, 5%, Radial Lead	MCPRM05WJP103B00
Metal Film Resistor, 100k Ω , 5W, 5%, Radial Lead	MCPRM05WJP104B00
Metal Film Resistor, 110 Ω , 5W, 5%, Radial Lead	MCPRM05WJP111B00
Metal Film Resistor, 120 Ω , 5W, 5%, Radial Lead	MCPRM05WJP121B00
Metal Film Resistor, 130 Ω , 5W, 5%, Radial Lead	MCPRM05WJP131B00
Metal Film Resistor, 150 Ω , 5W, 5%, Radial Lead	MCPRM05WJP151B00
Metal Film Resistor, 1.5k Ω , 5W, 5%, Radial Lead	MCPRM05WJP152B00
Metal Film Resistor, 15k Ω , 5W, 5%, Radial Lead	MCPRM05WJP153B00
Metal Film Resistor, 200 Ω , 5W, 5%, Radial Lead	MCPRM05WJP201B00
Metal Film Resistor, 2k Ω , 5W, 5%, Radial Lead	MCPRM05WJP202B00
Metal Film Resistor, 20k Ω , 5W, 5%, Radial Lead	MCPRM05WJP203B00
Metal Film Resistor, 24k Ω , 5W, 5%, Radial Lead	MCPRM05WJP243B00
Metal Film Resistor, 25k Ω , 5W, 5%, Radial Lead	MCPRM05WJP253B00
Metal Film Resistor, 270 Ω , 5W, 5%, Radial Lead	MCPRM05WJP271B00
Metal Film Resistor, 2.7k Ω , 5W, 5%, Radial Lead	MCPRM05WJP272B00
Metal Film Resistor, 300 Ω , 5W, 5%, Radial Lead	MCPRM05WJP301B00
Metal Film Resistor, 3k Ω , 5W, 5%, Radial Lead	MCPRM05WJP302B00
Metal Film Resistor, 330 Ω , 5W, 5%, Radial Lead	MCPRM05WJP331B00
Metal Film Resistor, 3.3k Ω , 5W, 5%, Radial Lead	MCPRM05WJP332B00
Metal Film Resistor, 33k Ω , 5W, 5%, Radial Lead	MCPRM05WJP333B00
Metal Film Resistor, 36k Ω , 5W, 5%, Radial Lead	MCPRM05WJP363B00
Metal Film Resistor, 390 Ω , 5W, 5%, Radial Lead	MCPRM05WJP391B00
Metal Film Resistor, 3.9k Ω , 5W, 5%, Radial Lead	MCPRM05WJP392B00
Metal Film Resistor, 39k Ω , 5W, 5%, Radial Lead	MCPRM05WJP393B00
Metal Film Resistor, 430 Ω , 5W, 5%, Radial Lead	MCPRM05WJP431B00
Metal Film Resistor, 43k Ω , 5W, 5%, Radial Lead	MCPRM05WJP433B00

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

